





SYMBOL LEGEND		
SYMBOL	DESCRIPTION	
HVAC PIPING		
	HWS	HOT WATER SUPPLY
	HWR	HOT WATER RETURN
	TWS	TEMPERED WATER SUPPLY
	CWS	CHILLED WATER SUPPLY
	CWR	CHILLED WATER RETURN
	RL	REFRIGERANT LIQUID
	RS	REFRIGERANT SUCTION
	CDWS	CONDENSER WATER SUPPLY
	CDWR	CONDENSER WATER RETURN
	D	DRAIN LINE
	(E)	EXISTING PIPE
	///////// (E) //////////	EXISTING PIPE TO BE REMOVED

ABBREVIATIONS			
NOTE: ALL ABBREVIATIONS MAY NOT BE USED			
AD AIR COND APD BD BHP BTU BTU/H CFH CFM CLG COMP COND CV CW DIA DISCH DP DB (E) EER EFF EG ELEC ELEV ENT EVAP EWT EXT (F) FC FD FLA FPI FPM FPS FSD FT GAL GPH GPM HD HG HR HT HTG HP HW HZ ID IN KW LAT LBS LG LH LRA LVG LWT MBH	ACCESS DOOR AIR CONDITION(-ING, -ED) AIR PRESSURE DROP BALANCING DAMPER BRAKE HORSE POWER BRITISH THERMAL UNIT BTU/HOUR CUBIC FEET PER HOUR CUBIC FEET PER MINUTE COOLING COMPONENT CONDENS(-ER, -ING, -ATION) CONTROL VALVE COLD WATER DIAMETER DISCHARGE DEPTH OR DEEP DRY BULB TEMPERATURE (E) EXISTING EER ENERGY EFFICIENCY RATIO EFF EFFICIENCY EG ETHYLENE GLYCOL ELEC ELECTRIC ELEV ELEVATION ENT ENTERING EVAP EVAPORAT(-E, -ING, -ED, -OR) EWT ENTERING WATER TEMP EXT EXTERNAL (F) FUTURE FC FAHRENHEIT FD FLEXIBLE CONNECTION FC FIRE DAMPER FLA FULL LOAD AMPS FPI FINS PER INCH FPM FEET PER MINUTE FPS FEET PER SECOND FSD FIRE SMOKE DAMPER FT FEET GAL GALLON(S) GPH GALLONS PER HOUR GPM GALLONS PER MINUTE HD HEAD HG MERCURY HR HOUR HT HEIGHT HTG HEATING HP HORSE POWER HW HOT WATER HZ HERTZ(FREQUENCY) ID INSIDE DIAMETER IN INCH KW KILOWATT LAT LEAVING AIR TEMPERATURE LBS POUNDS LG LENGTH LH LATENT HEAT LRA LOCKED ROTOR AMPS LVG LEAVING LWT LEAVING WATER TEMP MBH THOUSAND BTU PER HOUR	MCA MFR MIN N/A NC NC NC NO NPSH NTS OA OD OZ PD PG PH PPM PRESS PSF PSI PSIA PSIG R RA RECIRC REFR REQD RPM RW SA SC SCW SF SH SL SP SPEC(S) SQ STD TEMP TSTAT V VAC VAV VEL VENT VFD WG WPD WB	MINIMUM CIRCUIT AMPS MANUFACTURER MINIMUM NOT APPLICABLE NORMALLY CLOSED NOISE CRITERIA NOT IN CONTRACT NORMALLY OPEN NET POSITIVE SUCTION HEAD NOT TO SCALE OUTSIDE AIR OUTSIDE DIAMETER OUNCE PRESSURE DROP OR DIFF. PROPYLENE GLYCOL PHASE PARTS PER MILLION PRESSURE POUNDS PER SQUARE FOOT POUNDS PER SQUARE INCH PSI ABSOLUTE PSI GAUGE R THERMAL RESISTANCE RA RETURN AIR RECIRCULATE REFRIGERATION REQUIRED REVOLUTIONS PER MINUTE RAINWATER SA SUPPLY AIR SHADING COEFFICIENT SOFT COLD WATER SAFETY FACTOR SENSIBLE HEAT SEA LEVEL STATIC PRESSURE SPECIFICATION(S) SQUARE STANDARD TEMPERATURE THERMOSTAT V VOLT VAC VACUUM VAV VARIABLE AIR VOLUME VEL VELOCITY VENT VENT, VENTILATION VFD VARIABLE FREQUENCY DRIVE WG WATER COLUMN WPD WATER GAUGE WPD WATER PRESSURE DROP WB WET BULB

DEFINITIONS	
NOTE: ALL DEFINITIONS MAY NOT BE USED.	
INDICATED: THE TERM "INDICATED" REFERS TO GRAPHIC REPRESENTATIONS, NOTES, OR SCHEDULES ON THE DRAWINGS, OTHER PARAGRAPHS OR SCHEDULES IN THE SPECIFICATIONS, AND SIMILAR REQUIREMENTS IN THE CONTRACT DOCUMENTS. WHERE TERMS SUCH AS "SHOWN", "NOTED", "SCHEDULED", AND "SPECIFIED" ARE USED, IT IS TO HELP THE READER LOCATE THE REFERENCE, NO LIMITATION ON LOCATION IS INTENDED.	
DIRECTED: TERMS SUCH AS "DIRECTED", "REQUESTED", "AUTHORIZED", "SELECTED", "APPROVED", "REQUIRED", AND "PERMITTED" MEAN "DIRECTED BY THE ENGINEER", "REQUESTED BY THE ENGINEER", AND SIMILAR PHRASES.	
APPROVE: THE TERM "APPROVED", WHERE USED IN CONJUNCTION WITH THE ENGINEER'S ACTION ON THE CONTRACTOR'S SUBMITTALS, APPLICATIONS, AND REQUESTS, IS LIMITED TO THE ENGINEER'S DUTIES AND RESPONSIBILITIES AS STATED IN GENERAL AND SUPPLEMENTARY CONDITIONS.	
FURNISH: THE TERM "FURNISH" IS USED TO MEAN "SUPPLY AND DELIVER TO THE PROJECT SITE, READY FOR UNLOADING, UNPACKING, ASSEMBLY, INSTALLATION, AND SIMILAR OPERATIONS."	
INSTALL: THE TERM "INSTALL" IS USED TO DESCRIBE OPERATIONS AT PROJECT SITE INCLUDING THE ACTUAL "UNLOADING, UNPACKING, ASSEMBLY, ERECTION, PLACING, ANCHORING, APPLYING, WORKING TO DIMENSION, FINISHING, CURING, PROTECTING, CLEANING, AND SIMILAR OPERATIONS TO MAKE THE ITEM FULLY OPERATIONAL."	
PROVIDE: THE TERM "PROVIDE" MEANS "TO FURNISH AND INSTALL, COMPLETE AND READY FOR THE INTENDED USE."	
INSTALLER: AN "INSTALLER" IS THE CONTRACTOR OR AN ENTITY ENGAGED BY THE CONTRACTOR, EITHER AS AN EMPLOYEE, SUBCONTRACTOR, OR SUB-SUBCONTRACTOR, FOR PERFORMANCE OF A PARTICULAR CONSTRUCTION ACTIVITY, INCLUDING INSTALLATION, ERECTION, APPLICATION, AND SIMILAR OPERATIONS. INSTALLERS ARE REQUIRED TO BE EXPERIENCED IN THE OPERATIONS THEY ARE ENGAGED TO PERFORM.	

SYMBOL LEGEND	
SYMBOL	DESCRIPTION
VALVES, METERS, AND GAUGES	
	SHUT OFF VALVE
	GATE VALVE
	CHECK VALVE
	AUTO 2-WAY VALVE
	AUTO 3-WAY VALVE
	GLOBE VALVE
	BALL VALVE
	RELIEF VALVE
	CHAIN OPERATED GATE VALVE
	PRESSURE REDUCING VALVE
	BUTTERFLY VALVE
	SOLENOID VALVE
	ANGLE VALVE
	VENTURI
	BALANCING OR PLUG COCK
	FLOW SETTER
	EXPANSION VALVE (REFRIG.)
	TEMPERATURE SENSOR
	MANUAL AIR VENT
	STRAINER
	GAUGE COCK
	FLEXIBLE CONNECTION
	PRESSURE GAUGE
	THERMOMETER
	VICTAULIC COUPLING
	REDUCER CONCENTRIC
	REDUCER ECCENTRIC
	REFRIGERANT SITE GLASS
	REFRIGERANT STRAINER
	REFRIGERANT FILTER DRIER
	90° ELBOW UP
	90° ELBOW DOWN
	90° TEE UP
	90° TEE DOWN
	UNION
	CAPPED PIPE
	ANCHOR
	FLOAT AND THERMOSTATIC TRAP
HVAC SYMBOLS	
	THERMOSTAT
	TEMPERATURE SENSOR
	HUMIDISTAT
PLUMBING SYMBOLS	
	CATCH BASIN
	MANHOLE
	WALL HYDRANT
	HOSE BIBB
	CLEANOUT TO GRADE
	FLOOR CLEANOUT
	WALL CLEANOUT

SYMBOL LEGEND		
SYMBOL	DESCRIPTION	
DUCTWORK		
SINGLE LINE	DOUBLE LINE	DESCRIPTION
		RECTANGULAR SUPPLY DUCT UP
		RECTANGULAR SUPPLY DUCT DOWN
		RECTANGULAR RETURN DUCT UP
		RECTANGULAR RETURN DUCT DOWN
		RECTANGULAR EXHAUST DUCT UP
		RECTANGULAR EXHAUST DUCT DOWN
		ROUND DUCT UP
		ROUND DUCT DOWN
		ACOUSTICALLY LINED RECTANGULAR DUCT
		90° RECTANGULAR ELBOW WITH TURNING VANES
		90° RADIUS ELBOW R=1.5
		DUCT SIZE OR SHAPE TRANSITION
		OPPOSED BLADE BALANCING DAMPER (O.B.D.) IN RECT DUCT
		BUTTERFLY BALANCING DAMPER IN ROUND DUCTS
		COMBINATION TEE
		SPLITTER DAMPER
		SQUARE OR RECTANGULAR CEILING DIFFUSER
		ROUND CEILING DIFFUSER
		SIDEWALL REGISTER SUPPLY OR RETURN
		ROUND FLEXIBLE DUCT
		RETURN GRILLE
		EXHAUST GRILLE
		FIRE/SMOKE DAMPER
		FIRE DAMPER
		FLEXIBLE CONNECTION
		EXISTING DUCT
		DUCT TO BE REMOVED

GENERAL MECHANICAL NOTES	
	1. ALL CEILING DIFFUSERS SHOWN AS SUCH ARE CD-1, CFM AS NOTED, UNLESS OTHERWISE NOTED.
	2. ALL CEILING RETURN GRILLES SHOWN AS SUCH ARE RG-1 UNLESS OTHERWISE NOTED. PROVIDE SOUND BOOT
	3. ALL CEILING EXHAUST GRILLES SHOWN AS SUCH ARE EG-1, CFM AS NOTED, UNLESS OTHERWISE NOTED.
	4. DO NOT ROUTE DUCTS AND PIPES ABOVE ELECTRICAL PANELS. ALL ELECTRICAL PANELS MUST HAVE CLEAR ACCESS SPACE IN FRONT OF PANEL 4'-0" DEEP AND 6'-6" HIGH. DO NOT ROUTE DUCTS AND PIPES IN ELECTRICAL ROOMS, EXCEPT DUCTS AND PIPES SERVING THE ROOM OR WITHIN APPROPRIATE ENCLOSURE.
	5. COORDINATE EXACT LOCATIONS OF CEILING DIFFUSERS AND GRILLES WITH ARCHITECTURAL REFLECTED CEILING PLANS.
	6. ALL DUCT DIMENSIONS ARE INSIDE FREE AREA DIMENSIONS. ADJUST SHEET METAL DIMENSION FOR LINED DUCT.
	7. ALL FIRE DAMPERS SHOWN ARE 1-1/2 HOUR UNLESS OTHERWISE NOTED.
	8. IF CONTRACTOR ENCOUNTERS MATERIAL WHICH MAY CONTAIN ASBESTOS IMMEDIATELY STOP WORK IN THIS AREA AND NOTIFY THE OWNER.
	9. PROVIDE CEILING ACCESS PANELS AS REQUIRED WHERE MECHANICAL EQUIPMENT, VALVES, HEAT PUMPS, FIRE DAMPERS, ETC. ARE LOCATED ABOVE INACCESSIBLE CEILINGS. ACCESS PANELS TO BE LISTED AND FIRE RATED EQUAL TO OR GREATER THAN THE RATING OF THE ASSEMBLY THEY ARE INSTALLED IN.
	10. ALL DUCT AND FLUE PENETRATIONS THRU 1 HOUR ROOF ASSEMBLY TO BE ENCLOSED WITH 2 SHEET ROCK LAYERS FROM SHEET ROCK AT BOTTOM OF ROOF TRUSSES TO ROOF DECK.
	11. STEEL ROOF DECK SHALL NOT BE USED TO SUPPORT LOADS FROM PIPING, DUCTWORK OR EQUIPMENT, UNLESS NOTED OTHERWISE. HANGER LOADS LESS THAN 50 LBS. MAY BE HUNG FROM THE STEEL ROOF DECK IN CASES WHEN HANGING FROM THE STEEL ROOF DECK CANNOT BE AVOIDED; THE ATTACHMENT METHOD MUST DISTRIBUTE THE LOAD ACROSS THE DECK AS APPROVED BY THE STRUCTURAL ENGINEER.
	12. THE EQUIPMENT INSTALLER IS TO APPLY AND SIGN A CERTIFICATION LABEL TO EACH GAS-FIRED APPLIANCE, STATING THE APPLIANCE HAS BEEN ADJUSTED OR MODIFIED PER MANUFACTURER'S REQUIREMENTS FOR OPERATION AT THE PROJECT ALTITUDE AND WITH THE BTU-CONTENT OF THE AVAILABLE FUEL-GAS.
SYMBOL LEGEND	
SYMBOL	DESCRIPTION
REFERENCE AND LINE SYMBOLS	
	DETAIL INDICATOR: # INDICATES DETAIL NUMBER, SHEET INDICATES DRAWING SHEET WHERE DETAIL IS SHOWN.
	ELEVATION OR SECTION INDICATOR, EXTERIOR: # INDICATES ELEVATION OR SECTION NUMBER, SHEET INDICATES DRAWING SHEET WHERE ELEVATION OR SECTION IS SHOWN.
	ELEVATION OR SECTION INDICATOR, INTERIOR: # INDICATES ELEVATION OR SECTION NUMBER, SHEET INDICATES DRAWING SHEET WHERE ELEVATION OR SECTION IS SHOWN.
	DIFFUSER/GRILLE INDICATOR.
	DIFFUSER/GRILLE INDICATOR.
	NEW CONNECTION POINT TO EXISTING
MECHANICAL SCOPE OF WORK	
NEW CONSTRUCTION NOTES:	
ELECTRIC UNIT HEATERS WILL BE PLACED WATER ENTRY ROOMS AND MAIN BUILDING ENTRY LOCATIONS.	
ROOFTOP UNITS ARE TO BE INSTALLED WITHIN EXISTING EQUIPMENT WELLS ON ROOF OF EACH BUILDING. SUPPLY AND RETURN DUCTWORK IS TO ROUTE THROUGH EXISTING TRUSS SYSTEM. TERMINAL SUPPLY AND RETURN GRILLES ARE TO INCORPORATE INTEGRAL BALANCING DAMPERS.	
CLOTHES DRYER AND BATHROOM EXHAUST DUCTWORK IS TO TERMINATE AT UNDERSIDE OF EXISTING BUILDING OVERHANGS.	
THE NEW SYSTEM COMPONENTS WILL ALLOW FOR FUTURE OFFICE & TEMPORARY RESIDENT SPACES.	

MECH/PLUMB SHEET INDEX	
SHEET NO	SHEET TITLE
M01	MECHANICAL GENERAL NOTES & LEGEND
M02	MECHANICAL EQUIPMENT SPECIFICATIONS
M11	MECHANICAL SCHEDULES
M12	MECHANICAL DETAILS
M13	MECHANICAL DETAILS
M14	MECHANICAL DETAILS
M15	MECHANICAL DETAILS
M16	MECHANICAL DETAILS
M17	MECHANICAL DETAILS
M18	MECHANICAL DETAILS
P01	PLUMBING GENERAL NOTES & LEGEND
P02	PLUMBING EQUIPMENT SPECIFICATIONS
P11	PLUMBING SCHEDULES
P12	PLUMBING DETAILS
P13	PLUMBING DETAILS
P14	PLUMBING DETAILS
MP1D	MECH/PLUMB ROOF PLAN - BUILDING 'D'
M1D	MECHANICAL PLAN - BUILDING 'D'
P1D	PLUMBING PLAN - BUILDING 'D'

Donald L. Welch
Architect
7533 Sandy Land Lane
Midvale, Utah 84047
801.548-6391
dwelch5977@msn.com

SPECTRUM
ENGINEERS
324 S. State St., Suite 400
Salt Lake City, UT 84111
800-678-7077
801-328-5151
fax: 801-328-5155
www.spectrum-engineers.com

THE DESIGNS SHOWN AND DESCRIBED HEREIN INCLUDING ALL TECHNICAL DRAWINGS, GRAPHIC REPRESENTATION & MODELS THEREOF, ARE PROPRIETARY & CAN NOT BE COPIED, DUPLICATED, OR COMMERCIALY EXPLOITED IN WHOLE OR IN PART WITHOUT THE SOLE AND EXPRESS WRITTEN PERMISSION FROM DONALD L. WELCH ARCHITECT

THESE DRAWINGS ARE AVAILABLE FOR LIMITED REVIEW AND EVALUATION BY CLIENTS, CONSULTANTS, CONTRACTORS, GOVERNMENT AGENCIES, VENDORS, AND OFFICE PERSONNEL ONLY IN ACCORDANCE WITH THIS NOTICE.

consultant:

project:
Tenant Finish
for New
Brighton
Recovery
Campus
4905, 4911, 4915,
4925, 4931, & 4953
South 900 East
Salt Lake County,
Utah

date
April 24, 2017

revisions
PERMIT SET--December 28, 2016
ADDENDUM #1--January 04, 2017
ADDENDUM #3--January 11, 2017
ADDENDUM #4--January 17, 2017
ADDENDUM #5--January 20, 2017
ADDENDUM #7--February 24, 2017
ADDENDUM #8 - March 20, 2017
ADDENDUM #9 - April 11, 2017

data
project no:
drawn by:
checked by:
title
MECHANICAL
GENERAL NOTES
& LEGEND
sheet

M01

BUILDING 'D'

Building 'D' 4925 South 900 East Parcel # 22081850110000

MAKE-UP AIR UNIT SCHEDULE (2-STAGE HEATING/ EVAP COOLING) (BLDG 'D')													
SYMBOL	MANUFACTURER	MODEL #	CFM	VOLT/PH	EER	COOLING CAP HI/LOW (BTUH)	HEATING INPUT 1ST/2ND STAGES (BTUH)	ELECTRICAL			DIMENSIONS H X W X L	WEIGHT (LBS)	COMMENTS
								VOLT/PH	MCA (AMPS)	MAX FUSE			
MAU-1	SEE MANUFACTURER'S EQUIPMENT SCHEDULE BELOW												

MAU-1

Item	Qty	Description
1 ea		MAKE-UP AIR UNIT Fan #2 D76 - Heater D76 Low CFM Direct Fired Heater. Belt Drive. Supply Fan handles 1152 CFM @ 0.500" wc ESP, Fan runs at 1917 RPM. Heater supplies 99533 BTUs. 80°F Temperature Rise. [Fuel: Natural
		Gas] Supply Motor: 1.000 HP, 3 Phase, 208 V, 60Hz, 3.4 FLA, ODP (Open Drip Proof) Down Discharge - Air Flow Right -> Left x1 - Size # 1 Celdek Evaporative Cooler for Compact Direct-fired Heater. 26.75" Wide X 76.438" Long X 29.688" High. Includes intake hood with filters. For outdoor installation. x1 - RTC Solutions • 40-90°F Discharge Temp Control x1 - Gas Manifold for Commercial GM - BTU 0 - 241291 - 7 in. w.c. - 14 in. w.c., No Insurance Requirement (ANSI), BV250-44 x1 - Cooling Interlock Relay. 24VAC Coil. 120V Contacts. Locks out burner circuit when AC is energized. x1 - Gas Pressure Gauge, 0-35", 2.5" Diameter, 1/4" Thread Size x1 - Gas Pressure Gauge, -5 to +15 Inches Wc., 2.5" Diameter, 1/4" Thread Size x1 - Freeze Protection Drain Control kit for Evaporative Coolers. Includes 3-Way water solenoid valve 8316G064 (shipped loose), Pressure switch installed upstream of 2-way solenoid in unit, Brass Tee, 2 NPT half inch nipples, and two stage thermostat T678a-1015. Field wiring required by others for 3-way valve. For both Celdek and Standard V-bank type Configurations. x1 - Motorized Back Draft Damper 13" X 17" for D76 Compact Direct Fired Heaters w/Extended Shaft, Standard Galvanized Construction, 3/4" Rear Flange, TF1205 Actuator Included x1 - Curb CRB19.5X52X20INS Insulated On Fan # 2 Flat Curb x1 - Rail ADJUSTLEG-36 On Fan # 2 x1
1 ea		ELECTRICAL SYSTEM #1 SC-311110FP 3 Phase w/ control for 1 Exhaust Fan, 1 Supply Fan, Exhaust on in Fire, Lights out in Fire, Fan(s) On/Off Thermostatically Controlled. Room temperature sensor shipped loose for field installation. Includes 1 Duct Thermostat kit. x1 - Digital Rewire Lighting Relay Kit. Includes hood lighting relay & terminal blocks. Allows for up to 1400W of lighting each. x1
1 ea		DUCT WORK Duct Run #1 (P1) DW1258250LT Single Wall Duct 12" diameter, 58.250' long, flange at both ends. Stainless Steel. x1 (P2) DW1260AJDKIT Single Wall Duct Adjustable, 12" diameter, 59.5" long, flange at one end With a 12" Diameter - 4" Tall - Adjustable Collar - Stainless Steel. x1 (P3) DW12VESU18 Duct Vertical Support Assembly, 12" Duct, 18" Clearance To Combustibles. Parts are Zinc Coated. x1 (P4) DW2312TP Duct to Curb Transition, 23" Curb to 12" Duct, 16 GA Aluminized. Misc. non-standard transition plate. x1 3M-2000PLUS Duct - 3M Fire Barrier 2000 Plus Silicone - Used as sealant to Seal Duct Joints. x1 834680600587XL Duct - Duct insulation for zero clearance to combustibles - 300" x 24" x 1-1/2" Roll. Pyroscat Wrap. x2 BANDING.5 Duct - Fire Barrier Wrap Stainless Steel Banding .5" Width - 200 FT Per Roll. x1 DW12CLASY Duct "V" Clamp With new design 14 Ga Brackets, 12" Duct, Assembly. x2 SEAL.50-50 Duct - Fire Barrier Wrap Stainless Steel Banding Seal .5" Width. Quantity of 50. x1 TAPEALUM Duct - Fire Barrier Wrap Aluminum Foil Tape - 3" x 150' Roll. x1

TYPE I KITCHEN HOOD

Item	Qty	Description
01	1 ea	HOOD #1 Captive Aire Model No. HOOD #1 Hood #1 5424ND-2-PSP-F - 6ft 0" Long Exhaust-Only Wall Canopy Hood with Front Perforated Supply Plenum with Built-in 3" Back Standoff x1 - 430 SS Where Exposed x1 - Utility Cabinet on the Right Side x1 - FILTER - 20" tall x 16" wide Stainless Steel Captrate Solo filter with hook, ETL Listed. Particulate capture efficiency: 93% efficient at 9 microns, 72% efficient at 5 microns x4 - L55 Series E26 Canopy Light Fixture - High Temp Assembly, Includes Clear Thermal and Shock Resistant Globe (L55 Fixture), Bulbs By Others x2 - EXHAUST RISER - Factory installed 12" Diameter X 4" Height x1 - SUPPLY RISER - 10"x 28" Supply Riser with Volume Dampers x2 - 1/2 Pint Grease Cup New Style, Flanged Slotted x2 - LEFT QUARTER END PANEL 23" Top Width, 0" Bottom Width, 23" High 430 SS x1 - RIGHT QUARTER END PANEL 23" Top Width, 0" Bottom Width, 23" High 430 SS x1 - Electrical Package Installation in Utility Cabinet by Plant. x1

KITCHEN HOOD FIRE SUPPRESSION SYSTEM

Item	Qty	Description
1 ea		FIRE SUPPRESSION - Fire Suppression System Complete field installed UL300 hood fire suppression system (non union / non prevailing wage labor) Includes up to a 2" mechanical Gas valve, chrome sleeving on exposed piping, test, and Permits as required. Price is for a system that is installed during normal daytime weekday business hours. Any weekend or night work required will be extra. Gas valve needs to be installed by others prior to the fire system installation. Price is for surface mounted tension lines in conduit. If recessed tension lines are required, please consult CAS for revised price & requirements. Price includes two trips to jobsite. One trip is for installation, second trip is for test. Additional charges will apply for additional trips needed because of failed tests.
1 ea		FACTORY SERVICES Factory Services Service Design Verification for Direct Fired Heater x1 Service Design Verification for Evap Cooler x1 Service Design Verification for Exhaust Fan x1 Service Design Verification for Hood x1 Service Design Verification for Standard Electrical Control Package x1 Service Design Verification Mileage Charge: (27) x 2 = 54 total miles x1

ELECTRIC UNIT HEATER SCHEDULE

SYMBOL	MANUFACTURER AND MODEL NO.	LOCATION	ARRANGEMENT	CFM	ELECTRICAL				OPERATING WEIGHT (LBS.)	NOTES	ACCESSORIES AND REMARKS
					KW	MOTOR	VOLT	PHASE			
						H.P.					
EUH-1	TRANE UHEC03	WATER ENTRIES	VERTICAL	400	3.3	1/125	208	1	132	3	WALL HUNG
EUH-2	TRANE UHCA02	EXIT DOORS	HORIZONTAL	-	2.0	-	208	1	-	1,2	RECESSED, CEILING MOUNTED
EUH-3	TRANE UHAA15	CUSTODIAN	VERTICAL	-	1.5	-	208	1	22	1,2	RECESSED, WALL MOUNTED

NOTES:
(1) UNIT MOUNTED TAMPERPROOF THERMOSTAT
(2) UNIT MOUNTED DISCONNECT SWITCH
(3) PROVIDE WALL MOUNTED LINE VOLTAGE THERMOSTAT AND TAMPERPROOF WALL BRACKET

DIFFUSER AND GRILLE SCHEDULE

SYMBOL	MANUFACTURER AND MODEL NO.	LOCATION	CFM	OVERALL SIZE	NOTES	ACCESSORIES AND REMARKS
SG-1	TITUS 300R	CEILING	SEE PLANS	14 X 6 10 X 6	3,5	CEILING SUPPLY GRILLE W/ FIRE DAMPER
CD-1	TITUS PAS-FR	CEILING	SEE PLANS	24 X 24 12 X 12	2,5	CEILING DIFFUSER W/ FIRE DAMPER
RG-1	TITUS PAR-FR	CEILING	SEE PLANS	24 X 24 16 X 16	2,5	RETURN GRILLE W/ FIRE DAMPER
EG-1	TITUS 63F	EXTERIOR EXHAUST TERMINATION	SEE PLANS	8X6	4	EXHAUST DISCHARGE GRILLE, ALUMINUM
DG-1	TITUS CT-700L	DOOR TRANSFER	SEE PLANS	18 X 12	1	DOOR GRILLE

FIRE RATING NOTE: ALL CEILING DUCTWORK & DIFFUSER PENETRATIONS TO HAVE UL CLASSIFIED FIRE DAMPERS TO MAINTAIN FIRE RATING. (TYPICAL)

NOTES:
(1) PROVIDE AUXILIARY FRAME FOR TO ALLOW FOR FINISHED LOOK ON BOTH SIDES OF DOOR.
(2) PROVIDE FRAME AND BALANCING DAMPER ACCESSIBLE THROUGH GRILLE FOR HARDLID CEILING APPLICATIONS AS REQUIRED.
(3) PROVIDE DOUBLE DEFLECTION GRILLE WITH INTEGRAL BALANCING DAMPER.
(4) PROVIDE NECESSARY FRAME TO ALLOW FOR INSTALLATION ON BOTTOM SIDE OF EXISTING EXTERIOR OVERHANG.
(5) PROVIDE UL CLASSIFIED FIRE RATED CEILING DIFFUSER ASSEMBLY.

EXHAUST FAN SCHEDULE

SYMBOL	MANUFACTURER AND MODEL NO.	LOCATION	TYPE	FAN		ELECTRICAL				OPERATING WEIGHT (LBS.)	CONTROL METHOD	ACCESSORIES AND REMARKS
				CFM	ESP	MOTOR		VOLT	PHASE			
						H.P.	WATTS					
EF-1	PANASONIC FV-05-11VKS1	PRIVATE UNIT BATHROOMS	CEILING	110	0.5	-	57	115	1	27	1	CEILING MOUNTED W/ WHITE GRILLE
EF-2	PANASONIC FV-11-15VKS1	PUBLIC RESTROOM	CEILING	150	0.5	-	13	115	1	27	1	CEILING MOUNTED W/ WHITE GRILLE

CONTROL METHOD:
(1) CONTROLLED BY WALL SWITCH
(2) FAN RUNS CONTINUOUSLY DURING BUILDING OCCUPANCY
(3) CONTROLLED BY LINE VOLTAGE SPACE THERMOSTAT

ACCESSORIES:
(1) STANDARD DISCONNECT NEMA 1
(2) BACKDRAFT DAMPER
(3) FLEX DUCT CONNECTION
(4) FAN SPEED CONTROLLER 5A 120V PREWIRED
(5) RUBBER ISOLATOR SET (4)
(6) PROVIDE UL LISTED CEILING RADIATION DAMPER TO MATCH FAN TYPE (PANASONIC-RD05C3)

ROOFTOP UNIT SCHEDULE (2-STAGE HEATING/COOLING)

SYMBOL	MANUFACTURER	MODEL #	CFM	ESP	VOLT/PH	EER	COOLING CAP HI STAGE (BTUH)	HEATING INPUT (BTUH)	ELECTRICAL			DIMENSIONS H X W X L	WEIGHT (LBS)	COMMENTS
									VOLT/PH	MCA (AMPS)	MAX FUSE			
RTU-1	TRANE	4YC26036	1200	1.0	208/3	16.0	36,000	96,000	208/3	19.1	30 A	48" X 45" X 52"	550	HORIZONTAL SUPPLY/RETURN
RTU-2	TRANE	YHC047E3	1600	1.0	208/3	16.0	50,500	120,000	208/3	28.9	40 A	41" X 53" X 88"	800	HORIZONTAL SUPPLY/RETURN

(1) PROVIDE REMOTE PROGRAMMABLE THERMOSTAT IN LOCKABLE COVER.
(2) 0-25% MANUAL FRESH AIR DAMPER (BUILDING B RTUS)
(3) 0-100% HORIZONTAL ECONOMIZER (BUILDINGS A & C THRU F RTUS)
(4) 13" HIGH ROOF CURB/PLATFORM
(5) CRANKCASE HEATER FOR LOW AMBIENT COOLING
(6) PROVIDE INSULATED DUCT SHROUD ON ALL EXTERIOR DUCTWORK
(7) GAS PRESSURE REGULATOR & ISOLATION VALVE
(8) 120 V CONVENIENCE OUTLET INTEGRAL TO UNIT
(9) CONDENSER COIL HAIL GUARD
(10) NON-FUSED DISCONNECT INTEGRAL TO UNIT
(11) GAS & ELECTRIC FEEDS TO ENTER THROUGH BASE OF UNIT

DUCTLESS SPLIT SYSTEM HEAT PUMP

SYMBOL	MANUFACTURER	INDOOR UNIT				COOLING CAPACITY (BTUH)	HEATING CAPACITY (BTUH)	OUTDOOR UNIT						COMMENTS
		MODEL #	CFM	VOLT/PH	RLA (AMPS)			SYMBOL	VOLT/PH	MCA (AMPS)	MODEL #	HSPF	SEER	
DSS-1	LENNOX	MS8-HI-24P	590	208/1	0.24	25,000	26,000	CU-1	208/1	16.0	MS8-HO-24P	10.20	18.00	HIGH SIDEWALL STYLE (BLDGS. A, B, D, E & F)
DSS-2	LENNOX	MS8-HI-30P	705	208/1	0.40	30,000	33,000	CU-2	208/1	20.0	MS8-HO-30P	8.20	16.00	HIGH SIDEWALL STYLE (BLDG. C)

(1) PROVIDE REMOTE PROGRAMMABLE THERMOSTAT. BUILDINGS A, B, D, E & F MAX TEMP 85F (ADJ.) BUILDING C COOLING SETPOINT 70F (ADJ.) MAINTAIN 50F HEATING SETPOINT (ADJ)
(2) BUILT IN CONDENSATE PUMP / DISCHARGE CONDENSATE TO APPROVED LOCATION
(3) MULTI-SPEED FAN
(4) DEFROST CONTROL
(5) COMPRESSOR OVERCURRENT PROTECTION
(6) PROVIDE MANUFACTURER'S WALL CHANNEL (SPEEDICHANNEL SYSTEM) TO CONCEAL ALL REFRIGERANT PIPING EXPOSED TO VIEW AND EXTERIOR CONDITIONS.
(7) PROVIDE MANUFACTURER'S CONDENSER PAD 18 X 36 X 2

GREASE EXHAUST FAN SCHEDULE (BLDG 'D')

SYMBOL	MANUFACTURER AND MODEL NO.	LOCATION	TYPE	FAN		ELECTRICAL				OPERATING WEIGHT (LBS.)	CONTROL METHOD	ACCESSORIES AND REMARKS
				CFM	ESP	MOTOR		VOLT	PHASE			
						H.P.	WATTS					
GEF-1	SEE MANUFACTURER'S EQUIPMENT SCHEDULE BELOW											

GEF-1

Item	Qty	Description
1 ea		FAN #1 Fan #1 NCA14FA - Exhaust Fan NCA14FA Belt Drive Centrifugal Upblast Exhaust Fan with 15.75" wheel Exhaust Fan handles 1440 CFM @ -1.250" wc ESP, Fan runs at 1348 RPM. Exhaust Motor: 1.000 HP, 3 Phs, 208 V, 60Hz, 3.4 FLA, ODP (Open Drip Proof) x1 - Grease Cup for kitchen-duty centrifugal exhaust fans, Box Dimensions 17-1/8 L X 5-1/16 W X 3-3/4 H (18 GA.) (Includes Down Spout) x1 - Gasketing - Thermeez Woven Ceramic Tape - 1/4" x 1" with adhesive back - Max Temp 1500°F. To be applied between fan base and grease duct. Ships loose with fan. Gasket length supplied = perimeter of fan base. x1 - Curb CRB23x22E On Fan # 1 Flat Curb x1 - Hinged Base for Curb. Standard Hinge attached to curb. Used on Fans with wheels 20 inches or smaller. 12 GA Galvanized. x1 - Vented Base for Curb x1

Donald L. Welch
Architect
7533 Sandy Land Lane
Midvale, Utah 84047
801.548-6391
dwelch5977@msn.com




324 S. State St., Suite 400
Salt Lake City, UT 84111
800-678-7077
801-328-5151
fax: 801-328-5155
www.spectrum-engineers.com

THE DESIGNS SHOWN AND DESCRIBED HEREIN INCLUDING ALL TECHNICAL DRAWINGS, GRAPHIC REPRESENTATION & MODELS THEREOF, ARE PROPRIETARY & CAN NOT BE COPIED, DUPLICATED, OR COMMERCIALY EXPLOITED IN WHOLE OR IN PART WITHOUT THE SOLE AND EXPRESS WRITTEN PERMISSION FROM DONALD L. WELCH ARCHITECT

THESE DRAWINGS ARE AVAILABLE FOR LIMITED REVIEW AND EVALUATION BY CLIENTS, CONSULTANTS, CONTRACTORS, GOVERNMENT AGENCIES, VENDORS, AND OFFICE PERSONNEL ONLY IN ACCORDANCE WITH THIS NOTICE.

consultant:



project:

Tenant Finish
for New
Brighton
Recovery
Campus
4905, 4911, 4915,
4925, 4931, & 4953
South 900 East
Salt Lake County,
Utah

date

April 24, 2017

revisions

PERMIT SET-December 28, 2016
ADDENDUM #1-January 04, 2017
ADDENDUM #3-January 11, 2017
ADDENDUM #4-January 17, 2017
ADDENDUM #5-January 20, 2017
ADDENDUM #7-February 24, 2017
ADDENDUM #8 - March 20, 2017
ADDENDUM #9 - April 11, 2017

data

project no:

drawn by:

checked by:


title

MECHANICAL
SCHEDULES

sheet


M11

BUILDING 'D'




8 DIFFUSER CONNECTION

SCALE: NTS




9 DUCT HANGER

SCALE: NTS




10 TYP BRACING FOR ROUND DUCT

SCALE: NTS




11 ROOF CURB SEISMIC BRACE

SCALE: NTS



4 STANDARD CLIP ANGLES


SCALE: NTS



NOTES:
1. WHEN A COMBINATION OF DUCTS ARE USED IN LIEU OF ONE DUCT, AT LEAST 2 SIDES OF EACH DUCT MUST BE CONNECTED TO VERTICAL OR HORIZONTAL L's. (ADD HORIZONTAL L's IF REQUIRED.)

5 SIDE BRACING-RECTANGULAR DUCT

SCALE: NTS



6 MAKE-UP AIR UNIT DETAIL

SCALE: NTS

NOTE: PROVIDE SLOPED CURB, SERVICE PLATFORM, & RAILING PER MANUFACTURER'S RECOMMENDATIONS.

NOTE:
ALL PIPING IN 3/8\"/>


ALL FIELD EXPOSED PIPING SLEEVED IN CHROME

EXHAUST FAN TO REMAIN ON, MAKEUP AIR, GAS AND ALL ELECTRIC TO SHUT-DOWN IN SYSTEM ACTUATION.

NOZZLE PLACEMENT MEETS ANSUL UL300 CRITERIA


TEST LINKS TO BE DETERMINED BY INSTALLER

ELEC. EQUIP. -- NO GAS VALVE REQUIRED



7 FIRE SUPPRESSION SYSTEM


SCALE: NTS



NOTE: MECHANICAL EQUIPMENT TO SIT LEVEL. ORDER CURB TO COMPENSATE FOR ROOF SLOPE.

1 KITCHEN EXHAUST FAN DETAIL

SCALE: NTS




NOTES:

1. KITCHEN EXHAUST HOOD SHALL BE I.C.C. AND U.L. LISTED.
2. AUTOMATIC WET CHEMICAL FIRE SUPPRESSION SYSTEM SHALL BE INSTALLED
3. PROVIDE ACCESS OPENING OPPOSITE DUCT ACCESS DOORS, IN RATED ENCLOSURE. ACCESS DOORS TO MATCH ENCLOSURE IN FIRE PROTECTIVE RATING.

2 KITCHEN EXHAUST SYSTEM DETAIL

SCALE: NTS



NOTE: SIZES SHOWN ARE INSIDE DIMENSIONS

3 SECTION THROUGH TYPE 1 HOOD

SCALE: NTS

Donald L. Welch
Architect
7533 Sandy Land Lane
Midvale, Utah 84047
801.548-6391
dwlch5977@msn.com




324 S. State St., Suite 400
Salt Lake City, UT 84111
801-678-7077
801-328-5151
fax: 801-328-5155
www.spectrum-engineers.com

THE DESIGNS SHOWN AND DESCRIBED HEREIN INCLUDING ALL TECHNICAL DRAWINGS, GRAPHIC REPRESENTATION & MODELS THEREOF, ARE PROPRIETARY & CAN NOT BE COPIED, DUPLICATED, OR COMMERCIALY EXPLOITED IN WHOLE OR IN PART WITHOUT THE SOLE AND EXPRESS WRITTEN PERMISSION FROM DONALD L. WELCH ARCHITECT

THESE DRAWINGS ARE AVAILABLE FOR LIMITED REVIEW AND EVALUATION BY CLIENTS CONSULTANTS, CONTRACTORS, GOVERNMENT AGENCIES, VENDORS, AND OFFICE PERSONNEL ONLY IN ACCORDANCE WITH THIS NOTICE.

consultant:



project:

Tenant Finish
for New
Brighton
Recovery
Campus
4905, 4911, 4915,
4925, 4931, & 4953
South 900 East
Salt Lake County,
Utah

date

April 24, 2017

revisions

- PERMIT SET-December 28, 2016
- ADDENDUM #1-January 04, 2017
- ADDENDUM #3-January 11, 2017
- ADDENDUM #4-January 17, 2017
- ADDENDUM #5-January 20, 2017
- ADDENDUM#7-February 24, 2017
- ADDENDUM#8 - March 20, 2017
- ADDENDUM#9 - April 11, 2017

data

project no:

drawn by:

checked by:


title

MECHANICAL
DETAILS

sheet

M12

BUILDING 'D'



3 HORIZONTAL ECONOMIZER DETAIL (3 TON)
SCALE: NTS

Stainless Steel Drain Pan

For excellent corrosion and oxidation resistance, the optional stainless steel drain pan provides a cleanable surface that complement other IAQ solutions such as high efficiency filtration (MERV 8 or 13), demand control ventilation (CO₂), and hot gas reheat.

Powered or Unpowered Convenience Outlet



This option is a GFCI, 120V/15amp, 2 plug, convenience outlet, either powered or unpowered. This option can only be ordered when Through the Base Electrical with either the Disconnect Switch or Circuit Breaker option is ordered.
Note: Not available on 460V/575V units.

Through-the-Base Electrical Utility Access




An electrical service entrance shall be provided allowing electrical access for both control and main power connections inside the curb and through the base of the unit. Option will allow for field installation of liquid-tight conduit and an external field installed disconnect switch.



Factory provided through the base openings simplifies wiring and piping. Because these utility openings frequently minimize the number of roof penetration integrity of roofing materials is enhanced.


6 RTU ACCESSORY & INSTALLATION DETAIL
SCALE: NTS

Optional Equipment
BAYOSAH001,002A, 25% Outside Air Damper
(Replaces Filter/Coil Access Panel)



2 25% OUTSIDE AIR DAMPER (3 TON)
SCALE: NTS

Touchscreen Programmable Thermostat (2H/2C)





Two Heat/Two Cool programmable thermostat with touch screen digital display. Menu-driven programming. Effortless set-up. Program each day separately with no need to copy multiple days. All programming can be done on one screen. Easy to read and use. Large, clear backlit digital display.


5 RTU THERMOSTAT DETAIL
SCALE: NTS

RECOMMENDED SERVICE CLEARANCE MM/IN.		
		WITH ECONOMIZER
BACK SIDE	304.8 (12)	762.0 (30)
LEFT SIDE	762.0 (30)	914.4 (36)
RIGHT SIDE	914.4 (36)	-
FRONT SIDE	1066.8 (42)	-

CLEARANCE TO COMBUSTIBLE MATERIAL MM/IN.	
BOTTOM	0
BACK SIDE	25.4 (1)
LEFT SIDE	152.4 (6)
RIGHT SIDE	304.8 (12)
FRONT SIDE	304.8 (12)
TOP	914.4 (36)



1 ROOFTOP UNIT DETAIL (3 TON)
SCALE: NTS



4 ROOFTOP UNIT DETAIL (4 TON)
SCALE: NTS

Donald L. Welch
Architect
7533 Sandy Land Lane
Midvale, Utah 84047
801-328-5151
801-348-6391
dwl@sls77.com




324 S. State St., Suite 400
Salt Lake City, UT 84111
800-678-7077
801-328-5151
fax: 801-328-5155
www.spectrum-engineers.com

THE DESIGNS SHOWN AND DESCRIBED HEREIN INCLUDING ALL TECHNICAL DRAWINGS, GRAPHIC REPRESENTATION & MODELS THEREOF, ARE PROPRIETARY & CAN NOT BE COPIED, DUPLICATED, OR COMMERCIALY EXPLOITED IN WHOLE OR IN PART WITHOUT THE SOLE AND EXPRESS WRITTEN PERMISSION FROM DONALD L. WELCH ARCHITECT

THESE DRAWINGS ARE AVAILABLE FOR LIMITED REVIEW AND EVALUATION BY CLIENTS CONSULTANTS, CONTRACTORS, GOVERNMENT AGENCIES, VENDORS, AND OFFICE PERSONNEL ONLY IN ACCORDANCE WITH THIS NOTICE.

consultant:



project:

Tenant Finish
for New
Brighton
Recovery
Campus
4905, 4911, 4915,
4925, 4931, & 4953
South 900 East
Salt Lake County,
Utah

date

April 24, 2017

revisions

- PERMIT SET-December 28, 2016
- ADDENDUM #1-January 04, 2017
- ADDENDUM #3-January 11, 2017
- ADDENDUM #4-January 17, 2017
- ADDENDUM #5-January 20, 2017
- ADDENDUM #7-February 24, 2017
- ADDENDUM #8 - March 20, 2017
- ADDENDUM #9 - April 11, 2017

data

project no:

drawn by:

checked by:


title

MECHANICAL
DETAILS

sheet

M13


BUILDING 'D'



Captrate
Grease-Stop Solo Filter

RESISTANCE VS. AIRFLOW

2" Captrate Grease-Stop Solo Filter



Filter Detail

CAPTRATE

EXHAUST CFM=LENGTH OF HOOD X CFM/LIN.FT. (LOAD)

SUPPLY CFM=EXHAUST CFM X PERCENTAGE REQUIRED

TOTAL DUCT AREA=144 X CFM FPM(4)



DUCT LENGTH= TOTAL DUCT AREA DUCT DEPTH

*CAPTRATE-AIRE VENTILATOR DUCT SIZES ARE CALCULATED USING AN EXHAUST VELOCITY OF 1600-1800 FPM AND A SUPPLY VELOCITY OF 1000 FPM. PLEASE CONSULT FACTORY FOR MAXIMUM ALLOWABLE DUCT SIZES.


CALCULATIONS UTILIZED

CAPTRATE-AIRE HOODS ARE BUILT IN COMPLIANCE WITH:

- NFPA 96B
- ETL SANITATION
- ETL LISTED 3054804-001
- ETL IS LISTED TO ULC STANDARDS
- NSF



BUILDING CODES



Grease Cup will be supported by 2 studs in the inside wall of the hood. The cup will drain through a concealed venturi through and into the removable cup.

1/2 Pint Grease Cup Detail

1/2" DIA. ALL THREAD ROD CONNECTED TO HOOD, JOIST THROUGH ANOTHER HANGING ANGLE

1/2" DIA. HEAVY DUTY NUT ONE ABOVE AND ONE BELOW HANGING ANGLE

* ROD AND NUTS TO BE SUPPLIED BY INSTALLING CONTRACTOR. HANGING ANGLE IS PRE-FINISHED AT FACTORY.

ND-2 HANGING ANGLE DETAIL

HANGING ANGLES WILL BE LOCATED IN THE FOLLOWING LOCATIONS FOR WALL CANOPIES

HOOD STYLE	DIM FROM REAR	DIM FROM FRONT (24" High Hood)	DIM FROM FRONT (30" High Hood)
Wall Exhaust Only	2.25"	2.25"	2.25"
Wall Exhaust With MUA	4.166"	2.25"	2.25"
Back Shelf Exhaust Only	4.166"	2.25"	2.25"
Back Shelf Exhaust With MUA		2.25"	2.25"
Condensate	2.25"	2.25"	

HANGING ANGLE LOCATIONS

HOOD INFORMATION - Job#2871162

HOOD NO.	TAG	MODEL	LENGTH	MAX. COOKING TEMP.	EXHAUST PLENUM							TOTAL SUPPLY CFM	HOOD CONSTRUCTION	HOOD CANOPY	
					TYPE 3									END TO END	ROW
					TOTAL EXH. CFM	WIDTH	LENGTH	HEIGHT	DIA.	CFM	S.P.				
1		5424 ND-2-PSP-F	6' 0.00"	600 Deg.	1440			4"	12"	1440	-0.726"	1152	450 SS Where Exposed	ALONE	ALONE

PATENT NUMBERS

AC-PSP (United States) - US Patent 7965850 B2

AC-PSP Wall (Canada) - CA Patent 2820309P

AC-PSP Island (Canada) - CA Patent 2902990

HOOD INFORMATION

HOOD NO.	TAG	PLENUM (S)					LIGHT (S)			UTILITY CANOPY (S)					FIRE SYSTEM PPING	HOOD HANGING WEIGHT	
		TYPE	QTY.	HEIGHT	LENGTH	EFFICIENCY @ 9 MICRONS	QTY.	TYPE	WIRE GUARD	LOCATION	SIZE	FIRE SYSTEM		ELECTRICAL			SWITCHES
												TYPE	SIZE	MODEL #			QUANTITY
1		Capstrate Solo Filter	4	20"	16"	95% Solo Filter Spec.	2	L99 Series S28	NO	Back	12"16"124"			SC-5110P	1 Light 1 Fan	NO	468 LBS


HOOD OPTIONS

HOOD NO.	TAG	OPTION
1		LEFT QUARTER END PANEL 25" Top Width, 0" Bottom Width, 25" High 450 SS
		RIGHT QUARTER END PANEL 25" Top Width, 0" Bottom Width, 25" High 450 SS


PERFORATED SUPPLY PLENUM(S)

HOOD NO.	TAG	POS.	LENGTH	WIDTH	HEIGHT	TYPE	PERFOR (S)				S.P.
							WIDTH	LENGTH	DIA.	CFM	
1		Front	84"	16"	6"	MUA	10"	28"		976	0.154"
						MUA	10"	28"		976	0.154"


NOTE: MODEL ND-2 IS AN ETL LISTED HOOD
ETL LISTING IS 200 CFM/FT (600 DEGREES)
Q = ETL LISTING * 6' 0" = 1200 CFM < 1440 CFM (DESIGN)
MODEL ND-2 IS ETL LISTED WITH 1 EX RISER UP TO 16'




PLAN VIEW - Hood #1
6' 0.00" LONG 5424ND-2-PSP-F



SECTION VIEW - MODEL 5424ND-2-PSP-F
HOOD - #1



TYPICAL ANSUL R-102 SYSTEM LAYOUT



QUARTER END PANEL-ND-2

FOR QUESTIONS CONTACT
ERIC HOLMES
reg37@captiveneers.com
2688 S. Redwood Road, Suite 5
West Valley, UT 84119
PHONE: (801) 878-3677
FAX: (801) 877-9999




UTAH OFFICE

2688 S. Redwood Rd., Suite 5, West Valley, UT, 84119 PHONE: (801) 878-3677 FAX: (801) 877-9999 EMAIL: reg37@captiveneers.com

Brighton Recovery Kitchen
SALT LAKE CITY, UT, 84107

DATE: 12/27/2016
DWG.#: 2871162
DRAWN BY:
SCALE: 3/4" = 1'-0"
MASTER DRAWING

SHEET NO. 1



Terrell Roe
Restaurant Sales
Design Consultant
801-834-8896
terrell@standardrestaurant.com

3500 S West Temple
Salt Lake City, Utah 84115

Project Name
Brighton Recovery - Hood Ventilation drawing - Sheet 1

Date
20161227

Project
03-231

K-02.a

Donald L. Welch
Architect
7533 Sandy Land Lane
Midvale, Utah 84047
801.548-6391
dwelch5977@msn.com



324 S. State St., Suite 400
Salt Lake City, UT 84111
800-678-7077
801-328-5151
fax: 801-328-5155
www.spectrum-engineers.com

THE DESIGNS SHOWN AND DESCRIBED HEREIN INCLUDING ALL TECHNICAL DRAWINGS, GRAPHIC REPRESENTATION & MODELS THEREOF, ARE PROPRIETARY & CAN NOT BE COPIED, DUPLICATED, OR COMMERCIALY EXPLOITED IN WHOLE OR IN PART WITHOUT THE SOLE AND EXPRESS WRITTEN PERMISSION FROM DONALD L. WELCH ARCHITECT.

THESE DRAWINGS ARE AVAILABLE FOR LIMITED REVIEW AND EVALUATION BY CLIENTS, CONSULTANTS, CONTRACTORS, GOVERNMENT AGENCIES, VENDORS, AND OFFICE PERSONNEL ONLY IN ACCORDANCE WITH THIS NOTICE.

consultant:



project:

Tenant Finish
for New
Brighton
Recovery
Campus
4905, 4911, 4915,
4925, 4931, & 4953
South 900 East
Salt Lake County,
Utah

date
April 24, 2017

revisions

- PERMIT SET-December 28, 2016
- ADDENDUM #1-January 04, 2017
- ADDENDUM #3-January 11, 2017
- ADDENDUM #4-January 17, 2017
- ADDENDUM #5-January 20, 2017
- ADDENDUM #7-February 24, 2017
- ADDENDUM #8 - March 20, 2017
- ADDENDUM #9 - April 11, 2017

data





project no:
drawn by:
checked by:

title
MECHANICAL
DETAILS

sheet

M14

BUILDING 'D'



REVISIONS

NO.	DESCRIPTION	DATE
1	Issued for Construction	12/27/2016
2	Issued for Construction	12/27/2016
3	Issued for Construction	12/27/2016
4	Issued for Construction	12/27/2016
5	Issued for Construction	12/27/2016
6	Issued for Construction	12/27/2016
7	Issued for Construction	12/27/2016
8	Issued for Construction	12/27/2016
9	Issued for Construction	12/27/2016
10	Issued for Construction	12/27/2016
11	Issued for Construction	12/27/2016
12	Issued for Construction	12/27/2016
13	Issued for Construction	12/27/2016
14	Issued for Construction	12/27/2016
15	Issued for Construction	12/27/2016
16	Issued for Construction	12/27/2016
17	Issued for Construction	12/27/2016
18	Issued for Construction	12/27/2016
19	Issued for Construction	12/27/2016
20	Issued for Construction	12/27/2016
21	Issued for Construction	12/27/2016
22	Issued for Construction	12/27/2016
23	Issued for Construction	12/27/2016
24	Issued for Construction	12/27/2016
25	Issued for Construction	12/27/2016
26	Issued for Construction	12/27/2016
27	Issued for Construction	12/27/2016
28	Issued for Construction	12/27/2016
29	Issued for Construction	12/27/2016
30	Issued for Construction	12/27/2016
31	Issued for Construction	12/27/2016
32	Issued for Construction	12/27/2016
33	Issued for Construction	12/27/2016
34	Issued for Construction	12/27/2016
35	Issued for Construction	12/27/2016
36	Issued for Construction	12/27/2016
37	Issued for Construction	12/27/2016
38	Issued for Construction	12/27/2016
39	Issued for Construction	12/27/2016
40	Issued for Construction	12/27/2016
41	Issued for Construction	12/27/2016
42	Issued for Construction	12/27/2016
43	Issued for Construction	12/27/2016
44	Issued for Construction	12/27/2016
45	Issued for Construction	12/27/2016
46	Issued for Construction	12/27/2016
47	Issued for Construction	12/27/2016
48	Issued for Construction	12/27/2016
49	Issued for Construction	12/27/2016
50	Issued for Construction	12/27/2016
51	Issued for Construction	12/27/2016
52	Issued for Construction	12/27/2016
53	Issued for Construction	12/27/2016
54	Issued for Construction	12/27/2016
55	Issued for Construction	12/27/2016
56	Issued for Construction	12/27/2016
57	Issued for Construction	12/27/2016
58	Issued for Construction	12/27/2016
59	Issued for Construction	12/27/2016
60	Issued for Construction	12/27/2016
61	Issued for Construction	12/27/2016
62	Issued for Construction	12/27/2016
63	Issued for Construction	12/27/2016
64	Issued for Construction	12/27/2016
65	Issued for Construction	12/27/2016
66	Issued for Construction	12/27/2016
67	Issued for Construction	12/27/2016
68	Issued for Construction	12/27/2016
69	Issued for Construction	12/27/2016
70	Issued for Construction	12/27/2016
71	Issued for Construction	12/27/2016
72	Issued for Construction	12/27/2016
73	Issued for Construction	12/27/2016
74	Issued for Construction	12/27/2016
75	Issued for Construction	12/27/2016
76	Issued for Construction	12/27/2016
77	Issued for Construction	12/27/2016
78	Issued for Construction	12/27/2016
79	Issued for Construction	12/27/2016
80	Issued for Construction	12/27/2016
81	Issued for Construction	12/27/2016
82	Issued for Construction	12/27/2016
83	Issued for Construction	12/27/2016
84	Issued for Construction	12/27/2016
85	Issued for Construction	12/27/2016
86	Issued for Construction	12/27/2016
87	Issued for Construction	12/27/2016
88	Issued for Construction	12/27/2016
89	Issued for Construction	12/27/2016
90	Issued for Construction	12/27/2016
91	Issued for Construction	12/27/2016
92	Issued for Construction	12/27/2016
93	Issued for Construction	12/27/2016
94	Issued for Construction	12/27/2016
95	Issued for Construction	12/27/2016
96	Issued for Construction	12/27/2016
97	Issued for Construction	12/27/2016
98	Issued for Construction	12/27/2016
99	Issued for Construction	12/27/2016
100	Issued for Construction	12/27/2016

UTAH OFFICE

2888 S. Redwood Rd., Suite S, West Valley, UT 84119 PHONE: (801) 978-3077 FAX: (801) 227-5993 EMAIL: info@captivair.com

www.captivair.com

DATE: 12/27/2016

DWG.#: 287162

DRAWN BY:

SCALE: 3/4" = 1'-0"

MASTER DRAWING

SHEET NO. 3

System Design Verification (SDV)

If ordered, CAS Service will perform a System Design Verification (SDV) once all equipment has had a complete start up per the Operation and Installation Manual. Typically, the SDV will be performed after all inspections are complete.

Any field related discrepancies that are discovered during the SDV will be brought to the attention of the general contractor and corresponding trades on site. These issues will be documented and forwarded to the appropriate sales office. If CAS Service has to resolve a discrepancy that is a field issue, the general contractor will be notified and billed for the work. Should a return trip be required due to any field related discrepancy that cannot be resolved during the SDV, there will be additional trip charges.

During the SDV, CAS Service will address any discrepancy that is the fault of the manufacturer. Should a return trip be required, the general contractor and appropriate sales office will be notified. There will be no additional charges for manufacturer discrepancies.

FOR QUESTIONS CONTACT

2888 S. Redwood Rd., Suite S
West Valley, UT 84119
PHONE: (801) 978-3077
FAX: (801) 227-5993

STANDARD
Restaurant Supply

Terrill Roe
Restaurant Sales
Design Consultant
801-834-8896
terrill@standardrestaurant.com

3500 S West Temple
Salt Lake City, Utah 84115

Donald L. Welch
Architect
7533 Sandy Land Lane
Midvale, Utah 84047
801.548-6391
dwelch5977@msn.com




324 S. State St., Suite 400
Salt Lake City, UT 84111
800-678-7077
801-328-5151
fax: 801-328-5155
www.spectrum-engineers.com

THE DESIGNS SHOWN AND DESCRIBED HEREIN INCLUDING ALL TECHNICAL DRAWINGS, GRAPHIC REPRESENTATION & MODELS THEREOF, ARE PROPRIETARY & CAN NOT BE COPIED, DUPLICATED, OR COMMERCIALY EXPLOITED IN WHOLE OR IN PART WITHOUT THE SOLE AND EXPRESS WRITTEN PERMISSION FROM DONALD L. WELCH ARCHITECT

THESE DRAWINGS ARE AVAILABLE FOR LIMITED REVIEW AND EVALUATION BY CLIENTS CONSULTANTS, CONTRACTORS, GOVERNMENT AGENCIES, VENDORS, AND OFFICE PERSONNEL ONLY IN ACCORDANCE WITH THIS NOTICE.

consultant:



project:

Tenant Finish
for New
Brighton
Recovery
Campus
4905, 4911, 4915,
4925, 4931, & 4953
South 900 East
Salt Lake County,
Utah

date

April 24, 2017

revisions

- PERMIT SET-December 28, 2016
- ADDENDUM #1-January 04, 2017
- ADDENDUM #3-January 11, 2017
- ADDENDUM #4-January 17, 2017
- ADDENDUM #5-January 20, 2017
- ADDENDUM #7-February 24, 2017
- ADDENDUM #8 - March 20, 2017
- ADDENDUM #9 - April 11, 2017

data

project no:

drawn by:

checked by:

title

MECHANICAL
DETAILS


sheet

M16

BUILDING 'D'


ELECTRICAL PACKAGES - Job#2871162

NO.	TAG	PACKAGE #	LOCATION	SWITCHES		OPTION	FMS CONTROL			
				LOCATION	QUANTITY		TYPE	#	HP	VOLT
1		SC-9100FF	Utility Cabinet Rm	CH - Utility Cabinet Rm	1 Unit	Start Cabinet Thermostatic Control	Supply	3	1000	208




Hood Control Panel Specifications:

- Control panel shall be listed to UL standard UL90CA.
- The control enclosure shall be NEMA 1 rated and listed for installation inside of the exhaust hood utility cabinet. The control enclosure may be constructed of stainless steel or painted steel.
- Temperature probe(s) located in the exhaust duct riser(s) shall be constructed of stainless steel.
- A digital thermostat controller, listed to UL standard UL610C1-1, shall be provided to activate the hood exhaust fans dynamically based on a +/- 10 degree adjustable offset from the room temperature sensor. This function shall meet the requirements of IMC 507.2.1.1.
- A digital thermostat controller shall provide adjustable hysteresis settings to prevent cycling of the fans after the cooking appliances have been turned off and/ or the heat in the exhaust system is reduced.
- A digital thermostat controller shall provide an adjustable minimum fan run-time setting to prevent fan cycling.
- A digital thermostat controller shall disable the supply fan(s), activate the exhaust fan(s), activate the appliance shut-trip, and disable an electric gas valve automatically under the following conditions (as applicable):
 - a. Fire condition detected on a covered hood
 - b. Excessive temperature detected on any duct temperature sensor in the system (250 F adjustable)
- A digital thermostat controller shall allow for external BMS fan control via dry contacts (external control shall not override fan operation logic as required by code).
- An LCD interface shall be provided with the following features:
 - a. On/ Off push button fan & light switch activation
 - b. Integrated gas valve reset for electronic gas valves (no reset relay required)
 - c. Fan starter overload trip detection with audible & visual alarm notification
 - d. Temperature sensor failure/ mis-wiring detection with audible & visual alarm notification
 - e. A single low voltage Cat-5 RJ45 wiring connection



NOTES:
1. AUTOMATIC FIRE SUPPRESSION SYSTEM SHALL BE INSTALLED IN ACCORDANCE WITH NFPA REQUIREMENTS.



FOR QUESTIONS CONTACT:
ERIC HOLMES
eric@brightonrecovery.com
20955 S Redwood Road, Suite 5
West Valley, UT 84119
PHONE: (800) 515-5677
FAX: (800) 227-9999

REVISIONS

DATE: 12/27/2016

DWG.#: 2871162

DRAWN BY:

SCALE: 3/4" = 1'-0"

MASTER DRAWING

SHEET NO. 4

STANDARD Restaurant Supply

Terrell Roe
Restaurant Sales
Design Consultant
801-834-8896
terrell@standardrestaurant.com

3500 S West Temple
Salt Lake City, Utah 84115

K-02.d

Donald L. Welch
Architect
7533 Sandy Land Lane
Midvale, Utah 84047
801.548-6391
dwlch5977@msn.com

SPECTRUM ENGINEERS

324 S. State St., Suite 400
Salt Lake City, UT 84111
800-678-7077
801-328-5151
fax: 801-328-5155
www.spectrum-engineers.com

THE DESIGNS SHOWN AND DESCRIBED HEREIN INCLUDING ALL TECHNICAL DRAWINGS, GRAPHIC REPRESENTATION & MODELS THEREOF, ARE PROPRIETARY & CAN NOT BE COPIED, DUPLICATED, OR COMMERCIALY EXPLOITED IN WHOLE OR IN PART WITHOUT THE SOLE AND EXPRESS WRITTEN PERMISSION FROM DONALD L. WELCH ARCHITECT

THESE DRAWINGS ARE AVAILABLE FOR LIMITED REVIEW AND EVALUATION BY CLIENTS, CONSULTANTS, CONTRACTORS, GOVERNMENT AGENCIES, VENDORS, AND OFFICE PERSONNEL ONLY IN ACCORDANCE WITH THIS NOTICE.

consultant:

BENJAMIN J. SCHLUP
REGISTERED PROFESSIONAL ENGINEER
04-24-2017
No. 9520491
STATE OF UTAH

project:

Tenant Finish
for New
Brighton
Recovery
Campus
4905, 4911, 4915,
4925, 4931, & 4953
South 900 East
Salt Lake County,
Utah

date

April 24, 2017

revisions

PERMIT SET-December 28, 2016
ADDENDUM #1-January 04, 2017
ADDENDUM #3-January 11, 2017
ADDENDUM #4-January 17, 2017
ADDENDUM #5-January 20, 2017
ADDENDUM #7-February 24, 2017
ADDENDUM #8 - March 20, 2017
ADDENDUM #9 - April 11, 2017

data

project no:
drawn by:
checked by:

title

MECHANICAL
DETAILS

sheet

M17

BUILDING 'D'

DuctWork #1 Parts -- Job#2871162							
Item	Part #	QTY	SP	Weight	Volume	QTY	Description
P1	PW25625CLT	1440	-0.0558	25.11	1895.46	1	Single Wall Duct 12" diameter, 95.250" long, flange at both ends. Stainless Steel.
P2	PW25625CLT	1440	-0.0222	25.04	1895.46	1	Single Wall Duct Adjustable, 12" diameter, 99.5" long, flange at one end with a 12" Diameter - 4" Tall - Adjustable Collar - Stainless Steel.
P3	PW25625CLT			27.84		1	Duct Vertical Support Assembly, 12" Duct, 18" Clearance to Combustibles, Flange and Zinc Coated.
P4	PW25625CLT	1440	0	8.02	1895.46	1	Duct to Collar Transition, 25" Collar to 12" Duct, 16 GA Aluminum. Misc. non-standard transition plates.
P5	PW25625CLT	1440	-0.108				
P6	PW25625CLT			0.80		1	Duct - 5M Fire Barrier 20000 Plus Sloane - Used as standard to Seal Duct Joints.
P7	PW25625CLT			92.00		2	Duct - Duct insulation for zero clearance to combustibles - 500" x 24" x 1-1/2" Rb. Pyroscat Wrap.
P8	PW25625CLT			5.00		1	Duct - Fire Barrier Wrap Stainless Steel Banding 5" Wide - 200 FT Per Roll.
P9	PW25625CLT			1.25		2	Duct - 1/4" Clamp With non damage P4 (See P4) 12" Duct, Assembly.
P10	PW25625CLT			0.80		1	Duct - Fire Barrier Wrap Stainless Steel Banding Seal 5" Wide. Quantity of 50.
P11	PW25625CLT			0.25		1	Duct - Fire Barrier Wrap Aluminum Flat Caps - 5" x 180" Rb.
Total Weight				19712			

SHALL BE FACTORY BUILT DUCTWORK


- ALL DUCTWORK IS REQUIRED TO BE INSTALLED WITH THE MINIMUM SUPPORT SPACING LISTED BELOW.
- FOR A COMPLETE LIST OF APPROVED SUPPORT METHODS, SEE THE INSTALLATION AND OPERATION MANUAL.
- DUCTWORK SHALL SLOPE NOT LESS THAN 1/16" PER LINEAR FOOT TOWARDS THE HOOD OR AN APPROVED GREASE COLLECTION RESERVOIR.
- WHERE HORIZONTAL DUCTS EXCEED 75 FEET IN LENGTH, THE SLOPE SHALL NOT BE LESS THAN 5/16" PER LINEAR FOOT.

DUCT DIAMETER	HORIZONTAL WALL SUPPORT (LB)	VERTICAL WALL SUPPORT (LB)	VERTICAL CLIP SUPPORT (LB)
12"	10"	10"	24"

NOTES:

- KITCHEN EXHAUST HOOD SHALL BE I.C.C. AND U.L. LISTED.


DuctWork #1 SE View



Thermal Ceramics


Pyroscat Duct Wrap XL

Commercial Kitchen Grease Duct Enclosure System
Air Ventilation Duct Enclosure System
1 or 2 Hour Shaft Alternative / Zero Clearance to Combustibles




ABOVE DETAIL SHOWN AS SQUARE BUT WILL BE
INSTALLED ON ROUND GREASE DUCT



DuctWork #1 Front View




DuctWork #1 Top View



DuctWork #1 Side View



BUTT-JOINT/3\"/>



BUTT-JOINT/COLLAR

LEGEND

- Two Layers of Pyroscat Duct Wrap XL Blanket for Grease Duct Enclosures
One Layer of Pyroscat Duct Wrap XL Blanket for Air Ventilation Duct Enclosures
- Steel banding minimum 1/2" wide by 0.015" thick.
- Tight butt joints on inner layer
- Min. 3" overlap on perimeter and between adjacent blanket on outside layer
- Min. 3/8" diameter hanger rod
- Min. 2" x 2" x 1/8" angle for Grease Duct Enclosures
Min. 1-1/2" x 1-1/2" x 1/8" angle or SMACNA Equivalent for Air Ventilation Duct Enclosures
- Optional 6" FireMaster Pyroscat Duct Wrap XL collar

The integrity of Pyroscat duct systems is limited to the quality of the installation.

REVISIONS

DESCRIPTION	DATE

UTAH OFFICE
2888 S. Redwood Rd., Suite S, West Valley, UT, 84119 PHONE: (801) 875-3677 FAX: (801) 227-5953 EMAIL: reg87@captiveare.com
www.captiveare.com

Brighton Recovery Kitchen
SALT LAKE CITY, UT, 84107


DATE: 12/27/2016
DWG#: 2871162
DRAWN BY:
SCALE:
3/4" = 1'-0"
MASTER DRAWING

SHEET NO.
5

STANDARD
Restaurant Supply

Terrill Roe
Restaurant Sales
Design Consultant
801-834-8896
terrill@standardrestaurant.com

3500 S West Temple
Salt Lake City, Utah 84115



FLOOR PLAN

Project Name
Brighton Recovery - Hood Ventilation drawing - Sheet 5

Date
20161227

K-02.e

Donald L. Welch
Architect
7533 Sandy Land Lane
Midvale, Utah 84047
801.548-6391
dwelch5977@msn.com

324 S. State St., Suite 400
Salt Lake City, UT 84111
800-678-7077
801-328-5151
fax: 801-328-5155
www.spectrum-engineers.com

THE DESIGNS SHOWN AND DESCRIBED HEREIN INCLUDING ALL TECHNICAL DRAWINGS, GRAPHIC REPRESENTATION & MODELS THEREOF, ARE PROPRIETARY & CAN NOT BE COPIED, DUPLICATED, OR COMMERCIALY EXPLOITED IN WHOLE OR IN PART WITHOUT THE SOLE AND EXPRESS WRITTEN PERMISSION FROM DONALD L. WELCH ARCHITECT

THESE DRAWINGS ARE AVAILABLE FOR LIMITED REVIEW AND EVALUATION BY CLIENTS CONSULTANTS, CONTRACTORS, GOVERNMENT AGENCIES, VENDORS, AND OFFICE PERSONNEL ONLY IN ACCORDANCE WITH THIS NOTICE.

consultant:

BENJAMIN J. SCHLUP
STATE OF UTAH
No. 9520491
04-24-2017

project:

Tenant Finish
for New
Brighton
Recovery
Campus
4905, 4911, 4915,
4925, 4931, & 4953
South 900 East
Salt Lake County,
Utah

date
April 24, 2017

revisions

PERMIT SET-December 28, 2016

ADDENDUM #1-January 04, 2017

ADDENDUM #3-January 11, 2017

ADDENDUM #4-January 17, 2017

ADDENDUM #5-January 20, 2017

ADDENDUM #7-February 24, 2017

ADDENDUM #8 - March 20, 2017

ADDENDUM #9 - April 11, 2017

data

















project no:
drawn by:
checked by:

















































title
MECHANICAL
DETAILS















sheet

M18

BUILDING 'D'

SYMBOL LEGEND	
SYMBOL	DESCRIPTION
PLUMBING PIPING	
	SOIL, WASTE - ABOVE GRADE
	SOIL, WASTE - BELOW GRADE
	GREASE WASTE - ABOVE GRADE
	GREASE WASTE - BELOW GRADE
	VENT
	COLD WATER
	HOT WATER
	HOT WATER CIRCULATE
	STORM - ABOVE GRADE
	STORM - BELOW GRADE
	OVERFLOW STORM ABOVE GRADE
	OVERFLOW STORM BELOW GRADE
	VENT THRU ROOF
	EXISTING PIPE
	EXISTING PIPE TO BE REMOVED
	GAS

SYMBOL LEGEND	
SYMBOL	DESCRIPTION
VALVES, METERS, AND GAUGES	
	SHUT OFF VALVE
	GATE VALVE
	CHECK VALVE
	AUTO 2-WAY VALVE
	AUTO 3-WAY VALVE
	GLOBE VALVE
	BALL VALVE
	RELIEF VALVE
	CHAIN OPERATED GATE VALVE
	PRESSURE REDUCING VALVE
	BUTTERFLY VALVE
	SOLENOID VALVE
	ANGLE VALVE
	VENTURI
	BALANCING OR PLUG COCK
	FLOW SETTER
	EXPANSION VALVE (REFRIG.)
	GAS COCK
	MANUAL AIR VENT
	STRAINER
	GAUGE COCK
	FLEXIBLE CONNECTION
	PRESSURE GAUGE
	THERMOMETER
	VICTAULIC COUPLING
	REDUCER CONCENTRIC
	REDUCER ECCENTRIC
	REFRIGERANT SITE GLASS
	REFRIGERANT STRAINER
	REFRIGERANT FILTER DRIER
	90° ELBOW UP
	90° ELBOW DOWN
	90° TEE UP
	90° TEE DOWN
	UNION
	CAPPED PIPE
	ANCHOR
	FLOAT AND THERMOSTATIC TRAP
PLUMBING SYMBOLS	
	CATCH BASIN
	MANHOLE
	WALL HYDRANT
	HOSE BIBB
	CLEANOUT TO GRADE
	FLOOR CLEANOUT
	WALL CLEANOUT
	1/2 GRATE
	3/4 GRATE
	FULL GRATE

ABBREVIATIONS	
NOTE: ALL ABBREVIATIONS MAY NOT BE USED	
AD AC APD BD BHP BTU BTUH CFH CFM CLG COMP COND CV CW DIA DISCH DP DB (E) EER EFF EG ELEC ELEV ENT EVAP EWT EXT F FC FD FLA FFI FFM FFS FSD FT GAL GPH GPM HD HG HR HT HTG HP HW HZ ID IN KW LAT LBS LG LH LRA LVG LWT MAX MBH	ACCESS DOOR AIR CONDITION(-ING,-ED) AIR PRESSURE DROP BALANCING DAMPER BRAKE HORSE POWER BRITISH THERMAL UNIT BTU/HOUR CUBIC FEET PER HOUR CUBIC FEET PER MINUTE COOLING COMPONENT CONDENS(-ER,-ING,-ATION) CONTROL VALVE COLD WATER DIAMETER DISCHARGE DEPTH OR DEEP DRY BULB TEMPERATURE EXISTING ENERGY EFFICIENCY RATIO EFFICIENCY ETHYLENE GLYCOL ELECTRIC ELEVATION ENTERING EVAPORAT(-E,-ING,-ED,-OR) ENTERING WATER TEMP EXTERNAL FUTURE FAHRENHEIT FLEXIBLE CONNECTION FIRE DAMPER FULL LOAD AMPS FINS PER INCH FEET PER MINUTE FEET PER SECOND FIRE SMOKE DAMPER FEET GALLON(S) GALLONS PER HOUR GALLONS PER MINUTE HEAD MERCURY HOUR HEIGHT HEATING HORSE POWER HOT WATER HERTZ(FREQUENCY) INSIDE DIAMETER INCH KILOWATT LEAVING AIR TEMPERATURE POUNDS LENGTH LATENT HEAT LOCKED ROTOR AMPS LEAVING LEAVING WATER TEMP MAXIMUM THOUSAND BTU PER HOUR
MCA MFR MIN NA NC NC NIC NO NPSH NTS OA OD OZ PD PG PH PPM PRESS PSF PSI PSIA PSIG R RA RECIRC REFR REQD RPM RW SA SC SCW SF SH SL SP SPEC SQ STD STM TEMP TD TOT TSTAT V VAC VAV VEL VENT VERT VOL WIC WG WPD WTR WT WB	MINIMUM CIRCUIT AMPS MANUFACTURER MINIMUM NOT APPLICABLE NORMALLY CLOSED NOISE CRITERIA NOT IN CONTRACT NORMALLY OPEN NET POSITIVE SUCTION HEAD NOT TO SCALE OUTSIDE AIR OUTSIDE DIAMETER OUNCE PRESSURE DROP PROPYLENE GLYCOL PHASE PARTS PER MILLION PRESSURE POUNDS PER SQUARE FOOT POUNDS PER SQUARE INCH PSI ABSOLUTE PSI GAUGE THERMAL RESISTANCE RETURN AIR RECIRCULATE REFRIGERATION REQUIRED REVOLUTIONS PER MINUTE RAINWATER SUPPLY AIR SHADING COEFFICIENT SOFT COLD WATER SAFETY FACTOR SENSIBLE HEAT SEA LEVEL STATIC PRESSURE SPECIFICATION SQUARE STANDARD STEAM TEMPERATURE TEMP. DROP OR DIFF. TOTAL THERMOSTAT VENT VACUUM VARIABLE AIR VOLUME VELOCITY VENT, VENTILATION VERTICAL VOLUME WATER COLUMN WATER GAUGE WATER PRESSURE DROP WATER WEIGHT WET BULB TEMP
SYMBOL LEGEND	
SYMBOL	DESCRIPTION
REFERENCE AND LINE SYMBOLS	
	DETAIL INDICATOR: # INDICATES DETAIL NUMBER, SHEET INDICATES DRAWING SHEET WHERE DETAIL IS SHOWN.
	ROOM OR SPACE NUMBER.
	KEYNOTE INDICATOR.
	REVISION INDICATOR.
	EQUIPMENT INDICATOR.
	PLUMBING FIXTURE INDICATOR.
	DIFFUSER/GRILLE INDICATOR.
	DIFFUSER/GRILLE INDICATOR.
	BREAK, STRAIGHT
	BREAK, ROUND.
	MATCH LINE INDICATOR
	HIDDEN FEATURES LINE: HIDDEN, THIN LINE.
	CONTRACT LIMIT LINE: DASHDOT, WIDE LINE.
	NEW CONNECTION POINT TO EXISTING


PLUMBING SCOPE OF WORK
DEMOLITION NOTES: PLUMBING CONTRACTOR TO UTILIZE SELECTIVE DEMOLITION APPROACH. MANY AREAS INCLUDE PLUMBING EQUIPMENT AND ACCESSORIES LOCATED ABOVE HARDLID CEILINGS OR WITHIN INACCESSIBLE SPACES. FIELD TRACING OF DEMOLITION IS REQUIRED. ALL EXISTING PLUMBING FIXTURES AND ACCESSORIES ARE TO BE REMOVED TO ALLOW FOR NEW TENANT SPACES. ALL PLUMBING EQUIPMENT, FIXTURES, PIPING, AND ACCESSORIES THAT ARE CURRENTLY ABANDONED IN PLACE ARE TO BE REMOVED. ALL STORM WATER / ROOF DRAINAGE PIPING WITHIN THE BUILDING IS TO REMAIN UNCHANGED. EXISTING GAS METERS TO REMAIN. EXISTING GAS PIPING SEGMENTS MAY BE REUSED IF SIZING AND ROUTING ARE SIMILAR TO NEW PIPING LAYOUT. PUBLIC UTILITY COMPANY TO VERIFY NATURAL GAS CAPACITIES AND ASSOCIATED PRESSURES. CAP/REPLACE ALL WASTE AND VENT LINES BACK TO NEAREST MAIN TO ALLOW FOR FUTURE CONNECTIONS. NEW CONSTRUCTION NOTES: NEW WATER ENTRIES WILL BE INSTALLED AS INDICATED ON PLANS. ALL DOMESTIC COLD WATER AND FIRE WATER PIPING SEGMENTS EXPOSED TO ENVIRONMENT ARE TO BE INSULATED AND HEAT TRACED FOR FREEZE PROTECTION. ALL EXISTING STORM DRAIN TERMINATIONS ARE TO CONNECT TO CIVIL DRAINAGE SYSTEM. ALL GREASE WASTE PIPING DESIGNATED TO SERVE FUTURE WARMING KITCHEN WILL TIE INTO NEW GREASE INTERCEPTOR AS SHOWN ON CIVIL DRAWINGS. A VENT LINE FOR THE GREASE INTERCEPTOR WILL BE PROVIDED AND WILL TERMINATE THROUGH ROOF OF BUILDING 'D'. THE NEW SYSTEM COMPONENTS WILL ALLOW FOR FUTURE OFFICE AND TEMPORARY RESIDENT SPACES AS INDICATED ON PLANS. DOMESTIC WATER, WASTE, AND GREASE WASTE LINES (AS APPLICABLE) WILL BE PROVIDED TO EACH BUILDING AS INDICATED. HEATING OF DOMESTIC WATER WILL BE PROVIDED BY INDIVIDUAL BUILDING WATER HEATERS. DOMESTIC COLD WATER SUBMETERS TO BE INSTALLED IN EACH BUILDING'S WATER ENTRY ROOM. VERIFY NEED WITH OWNER PRIOR TO INSTALLATION.

FIRE PROTECTION SCOPE OF WORK
NEW CONSTRUCTION NOTES: NEW FIRE ENTRIES TO BE INSTALLED AS INDICATED ON PLANS. FIRE PROTECTION LINES TO BE ROUTED ON WARM SIDE OF BUILDING INSULATION. INSTALL FIRE PROTECTION SYSTEM PER NOTES INDICATED ON P02 OF THIS DRAWING SET. ALL BREEZEWAY SOFFITS TO INCORPORATE DRY PIPE FIRE PROTECTION SYSTEM FED FROM FIRE ENTRY ROOM PIPING AS REQUIRED. IN THE EVENT THAT ROUTING MAY PROVE DIFFICULT DUE TO EXISTING CONDITIONS A DRY-PIPE SYSTEM SHOULD BE EVALUATED. LOCATE AIR COMPRESSOR IN ASSOCIATED FIRE ENTRY ROOM AS REQUIRED. SEE SHEET P02 (SPEC SECTION 221316) AND SHEET P13 FOR FURTHER SYSTEM REQUIREMENTS & DETAILS. DIVISION 26 CONTRACTOR TO PROVIDE POWER TO ASSOCIATED SYSTEM FLOW SWITCH.

Donald L. Welch
Architect
7533 Sandy Land Lane
Midvale, Utah 84047
801.548-6391
dwelch5977@nsh.com


324 S. State St., Suite 400
Salt Lake City, UT 84111
800-678-7077
801-328-5151
fax: 801-328-5155
www.spectrum-engineers.com

THE DESIGNS SHOWN AND DESCRIBED HEREIN INCLUDING ALL TECHNICAL DRAWINGS, GRAPHIC REPRESENTATION & MODELS THEREOF, ARE PROPRIETARY & CAN NOT BE COPIED, DUPLICATED, OR COMMERCIALLY EXPLOITED IN WHOLE OR IN PART WITHOUT THE SOLE AND EXPRESS WRITTEN PERMISSION FROM DONALD L. WELCH ARCHITECT
THESE DRAWINGS ARE AVAILABLE FOR LIMITED REVIEW AND EVALUATION BY CLIENTS CONSULTANTS, CONTRACTORS, GOVERNMENT AGENCIES, VENDORS, AND OFFICE PERSONNEL ONLY IN ACCORDANCE WITH THIS NOTICE.

consultant:


project:
Tenant Finish
for New
Brighton
Recovery
Campus
4905, 4911, 4915,
4925, 4931, & 4953
South 900 East
Salt Lake County,
Utah

date
April 24, 2017

revisions
PERMIT SET-December 28, 2016
ADDENDUM #1-January 04, 2017
ADDENDUM #3-January 11, 2017
ADDENDUM #4-January 17, 2017
ADDENDUM #5-January 20, 2017
ADDENDUM#7-February 24, 2017
ADDENDUM#8 - March 20, 2017
ADDENDUM#9 - April 11, 2017

data
project no:
drawn by:
checked by:
title
PLUMBING
GENERAL NOTES
& LEGEND
sheet

P01
BUILDING 'D'

PLUMBING SPECIFICATIONS

220100 - BASIC PIPING MATERIALS & METHODS

- CORE CUT ALL PIPE PENETRATION OF EXISTING MASONRY OR CONCRETE WALLS AND FLOORS. SLEEVE ALL PENETRATIONS THROUGH NEW WALLS AND FLOORS. SEAL ALL PENETRATIONS WATER TIGHT WITH SILICONE SEALANT. USE FIRE RATED SEALANT (3M "FIRE BARRIER" OR EQUAL) FOR 1 HOUR OR 2 HOUR PENETRATIONS.
- CAULK AROUND ALL PIPING THAT PASSES THROUGH FIRE-RATED PARTITIONS WITH A NON-HARDENING CAULKING SIMILAR TO 3M "FIRE BARRIER".
- SEAL ALL PIPING THROUGH WALLS AIR TIGHT.

220533 - HEAT TRACING CABLE

- PROVIDE RAYCHEM ELECTRIC SELF REGULATING HEATING CABLE WITH ALL NECESSARY ACCESSORIES TO MAINTAIN THE TEMPERATURE IN THE TRACED PIPE SYSTEM AT 45°F.
- FOR DOMESTIC HOT WATER USE, THE CABLE SHALL BE DESIGNED, MANUFACTURED AND U.L. LISTED FOR DOMESTIC HOT WATER TEMPERATURE MAINTENANCE.
- CABLE SHALL CONSIST OF TWO (2) 16-AWG NICKEL-COATED COPPER BUS WIRES EMBEDDED IN A RADIATION-CROSSLINKED CONDUCTIVE POLYMER CORE. IT SHALL BE COVERED BY A RADIATION-CROSSLINKED, POLYOLEFIN, DIELECTRIC JACKET SURROUNDED BY A POLYMER-COATED ALUMINUM WRAP, AND ENCLOSED IN A TINNED COPPER BRAID OF 14 AWG EQUIVALENT WIRE SIZE. THE BRAID SHALL BE COVERED WITH A (NOMINAL) 40-MIL POLYOLEFIN OUTER JACKET, COLOR CODED FOR EASY IDENTIFICATION.

220548 - VIBRATION ISOLATION AND SEISMIC

- ALL PLUMBING EQUIPMENT AND PIPING MUST BE VIBRATION ISOLATED AND SEISMICALLY BRACED FOR THE SITE SPECIFIC SEISMIC DESIGN CATEGORY AND SEISMIC USE GROUP, IN ACCORDANCE WITH THE LATEST ADOPTED EDITIONS OF THE BUILDING CODES AND ASHRAE. PROVIDE SEISMIC PRODUCTS BY AMBER-BOOTH OR MASON INDUSTRIES.
- IN GENERAL, PROVIDE SPRING MOUNTS TO ATTENUATE LOW FREQUENCY SOUND AND VIBRATION. PROVIDE NEOPRENE PADS TO ATTENUATE HIGH FREQUENCY SOUND
- VIBRATION: SEISMIC BRACING/MOUNTING CAN BE COMBINED WITH VIBRATION ISOLATION AS APPLICABLE.
- CONTRACTOR MANUFACTURED SEISMIC BRACING/RESTRAINT METHODS ARE NOT ACCEPTABLE.
- PROVIDE A SIGNED AND STAMPED LETTER FROM A PROFESSIONAL ENGINEER CERTIFYING THAT THE SUPPLIED PRODUCTS ARE CORRECT FOR THE APPLICATION AND THAT THE INSTALLATION IS IN COMPLIANCE WITH ALL APPLICABLE CODES.

220719 - INSULATION

- PIPE INSULATION: SNAP-ON GLASS FIBER TYPE WITH VAPOR JACKET. SEAL ALL ENDS AND JOINTS TO PROVIDE A COMPLETELY SEALED SYSTEM. ALTERNATIVELY, FOR INTERIOR WATER PIPING, USE FLEXIBLE UNICELLULAR ASTM 534 TYPE 1 INSULATION. USE 1" THICKNESS FOR PIPE UP TO 2"Ø AND 1-1/2" FOR PIPE OVER 2"Ø
- PROVIDE ADA COMPLIANT FIXTURES WITH SNAP ON ADA ARTICLE 4.19 22FF COMPLIANT WHITE INSULATION. TRUEBRO NV GUARD, BASIN GUARD OR LAV SHIELD.
- THERMAL AND SOUND INSULATION AND COVERING WHICH ARE INSTALLED AND EXPOSED SPACES AND COVERING PIPE AND TUBING SHALL BE TESTED IN ACCORDANCE WITH ASTM E 84 AND HAVE A FLAME SPREAD OF 0-25 AND A SMOKE INDEX OF 0-450.
- THERMAL AND SOUND INSULATION AND COVERING OVER PIPE AND TUBING WHICH ARE INSTALLED IN CONCEALED PLENUM SPACES SHALL BE TESTED IN ACCORDANCE WITH ASTM E 84 AND HAVE A FLAME SPREAD OF 0-25 AND A SMOKE INDEX OF 0-50.

221116 - WATER DISTRIBUTION PIPING

- UNDERGROUND WATER PIPING:

2" AND SMALLER:
ASTM 88 TYPE "K" COPPER WITH A MINIMUM NUMBER OF SOLDERED JOINTS. USE 95-5 TIN ANTIMONY COPPER SOLDER.

2-1/2" AND LARGER:
PVC AWWA 900 CLASS 100 WITH SOLVENT CEMENTED JOINTS, OR PB PLASTIC PIPE ASTM D3309 SDR 11 WITH HEAT FUSION JOINTS.
- NO TYPE "M" OR "DWV" COPPER IS TO BE USED IN THIS PROJECT.
- ALL ABOVE GROUND HOT AND COLD WATER PIPING:
ASTM B 88 TYPE "L" COPPER, WITH WROUGHT COPPER FITTINGS AND SOLDERED WITH 95-5 TIN-ANTIMONY SOLDER.
- INSTALL PIPE HANGERS WITH THE FOLLOWING MINIMUM ROD SIZES AND MAXIMUM SPACING. UPON COMPLETION OF HANGER INSTALLATION, ALL ADJUSTMENTS HAVING THE POSSIBILITY OF TURNING SHALL BE LOCKED SECURELY IN PLACE BY DOUBLE NUTTING AT THE HANGER ROD ATTACHMENT TO THE STRUCTURE, AND AT THE PIPE HANGER.

NOM. PIPE SIZE-INCHES	MAX SPAN-FT.	MIN. ROD SIZE-INCHES
1	7	3/8
1-1/2	9	3/8
2	10	3/8
3	12	1/2
4	14	5/8
6	17	3/4
- ALL PIPE HANGERS AND EQUIPMENT SUPPORTS SHALL BE LOCATED A MINIMUM DISTANCE OF 2" FROM ANY REFRIGERANT PIPE.
- ALL PLUMBING FIXTURES CONNECTED TO A POTABLE WATER SYSTEM WITH HOSE CONNECTIONS ON THE OUTLET SIDE AND OWNER FURNISHED EQUIPMENT WITH DIRECT CONNECTIONS, SHALL BE PROVIDED WITH BACKFLOW PREVENTION.

PLUMBING SPECIFICATIONS

221316 - DRAINAGE AND VENT SYSTEMS

- UNDERGROUND BUILDING DRAIN PIPE AND FITTINGS:
A. NO HUB ABS OR PVC PLASTIC PIPE AND FITTINGS PER ASTM D2661 WITH ASTM D2235 SOLVENT OR
B. ASTM A74 SERVICE WEIGHT, HUB AND SPIGOT CAST IRON SOIL PIPE, OR ASTM A888 (OR CISPI 301) HUBLESS CAST IRON SOIL PIPE WITH ASTM C564 HEAVY DUTY SHIELDED STAINLESS STEEL COUPLINGS.

A. NO ASTM D2729 PIPE SHALL USED UNDERGROUND.
- ABOVE GROUND SANITARY DRAINAGE AND VENT PIPING, IN ALL AREAS EXCEPT AIR PLENUMS AND EXCEPT IN A FIRE RATED BUILDING, SHALL BE ABS TYPE DWV PLASTIC PIPE AND FITTINGS PER ASTM D2661 WITH ASTM D2265 SOLVENT, OR PVC PLASTIC PIPE AND FITTINGS PER ASTM D2665 WITH ASTM D2564 SOLVENT, OR SERVICE WEIGHT, NO HUB CAST IRON COUPLED PIPE AND FITTINGS WITH COMPRESSION TYPE NEOPRENE GASKETS AND STAINLESS STEEL BANDS.
- FORCE SEWER MAINS UP TO 4" SHALL BE TYPE L HARD COPPER TUBE WITH WROUGHT COPPER PRESSURE FITTINGS AND SOLDERED JOINTS, OR DUCTILE IRON PIPE AND FITTINGS WITH MECHANICAL JOINTS.
- ALL SANITARY DRAINAGE AND VENT PIPING INSIDE AIR PLENUMS AND ANYWHERE IN A FIRE RATED BUILDING SHALL BE NO HUB SERVICE WEIGHT CAST IRON COUPLED PIPE AND FITTINGS WITH COMPRESSION TYPE NEOPRENE GASKETS AND STAINLESS STEEL BANDS. ASTM B306 COPPER PIPE MAY BE USED WITH SOLDERED JOINTS FOR PIPE 3" AND SMALLER.
- ABOVE GROUND ROOF DRAIN LINES, EXCEPT IN AIR PLENUMS AND ANYWHERE IN A FIRE RATED BUILDING, SHALL BE ABS TYPE DWV PLASTIC PIPE AND FITTINGS PER ASTM D2661 WITH ASTM D2255 SOLVENT, OR PV C PLASTIC PIPE PER ASTM D2665 WITH ASTM D2564 SOLVENT.
- ALL ROOF DRAIN LINES INSIDE AIR PLENUMS, OR ANYWHERE IN A FIRE RATED BUILDING, SHALL BE SERVICE WEIGHT CAST IRON PIPE TO CISPI STANDARD 301.
- ALL ROOF DRAIN LINES SHALL BE FULLY INSULATED.
- OVERFLOW ROOF DRAINS SHALL DAYLIGHT 18" ABOVE THE SURROUNDING HORIZONTAL AREA.
- INSTALL SANITARY DRAIN LINES 2-1/2" AND LESS WITH A SLOPE OF 2%. INSTALL SANITARY DRAIN LINES 3"-6" WITH A SLOPE OF NOT LESS THAN 1%.
- SLOPE ROOF DRAIN LINES DOWN IN DIRECTION OF FLOW, 1/8" PER FOOT (1%).
- CLEANOUTS

A. FINISHED WALL CLEANOUTS: SMITH FIGURE 4472 COMPLETE WITH CAST BRONZE TAPER THREADED PLUG, STAINLESS STEEL COVER AND SCREW.
B. FLOOR CLEANOUTS (UNFINISHED AREAS): SMITH FIGURE 4223 DUCO CAST IRON CLEANOUT WITH ROUND ADJUSTABLE SCORIATED SECURED CAST IRON TOP, TAPER THREADED BRONZE PLUG AND SPIGOT OUTLET.
C. FINISHED FLOOR CLEANOUTS (CONCRETE FLOORS): SMITH FIGURE 4023 DUCO CAST IRON CLEANOUT WITH ADJUSTABLE SCORIATED SECURED NICKEL BRONZE TOP, TAPER THREADED CAST BRONZE PLUG AND SPIGOT OUTLET.
D. FINISHED FLOOR CLEANOUTS (CARPETED FLOORS): SMITH FIGURE 4023-Y SAME AS CONCRETE FLOORS WITH CARPET MARKER
E. FINISHED FLOOR CLEANOUTS (TILE FLOORS): SMITH FIGURE 4163 DUCO CAST IRON CLEANOUT WITH SQUARE ADJUSTABLE SECURED NICKEL BRONZE TOP WITH 1/8" RECESS, TAPER THREADED BRONZE PLUG AND SPIGOT OUTLET.
F. EXTERIOR CLEANOUTS (CLEANOUT TO GRADE): SMITH FIGURE 4253 DUCO CAST IRON CLEANOUT AND DOUBLE FLANGED HOUSING WITH HEAVY DUTY SECURED SCORIATED CAST IRON COVER WITH LIFTING DEVICE, TAPER THREADED BRONZE PLUG AND SPIGOT OUTLET.
- FLOOR DRAINS:

FD-1 FLOOR DRAIN: SMITH FIGURE 2010-BP CAST IRON BODY AND FLASHING COLLAR WITH PROTECTIVE CAP AND SQUARE NICKEL BRONZE ADJUSTABLE STRAINER HEAD WITH SECURED SQUARE HOLE GRATE, AND TRAP PRIMER CONNECTION.

FD-2 MECHANICAL ROOM DRAIN: SMITH FIGURE 2110-NB MEDIUM DUTY FLOOR DRAIN. CAST IRON BODY AND FLASHING COLLAR WITH NICKEL BRONZE BAR GRATE.
- ROOF DRAINS (AS REQUIRED IF REPLACEMENT IS NECESSARY)

RD-1 ROOF DRAIN: SMITH FIGURE 1010-ERC CAST IRON BODY WITH COMBINED FLASHING CLAMP AND CAST IRON GRAVEL STOP, CAST IRON DOME, EXTENSION, SUMP RECEIVER AND UNDERDECK CLAMP.

ORD-1 OVERFLOW ROOF DRAIN: SMITH FIGURE 1080-ERC CAST IRON BODY WITH FLASHING CLAMP, GRAVEL STOP, CAST IRON DOME, 2" HIGH CAST IRON WATER COLLAR, EXTENSION, SUMP RECEIVER AND UNDERDECK CLAMP.

DSN-1 DOWNSPOUT NOZZLE: SMITH FIGURE 1770 DOWNSPOUT NOZZLE. CAST BRONZE BODY AND FLANGE. PROVIDE BRONZE BOLTS TO SECURE NOZZLE TO WALL. INSTALL 12" ABOVE FOUNDATION UNLESS NOTED OTHERWISE.
- FIRE/WATER ENTRIES

FIRE ENTRY: WATTS 757DCDA OSY OR EQUAL. DOUBLE CHECK DETECTOR ASSEMBLY, TWO INDEPENDENTLY OPERATING TRI-LINK CHECK VALVES, TWO SHUTOFF VALVES, AND FOUR TEST COCKS. STAINLESS STEEL HOUSING AND SLEEVE. MAXIMUM WORKING PRESSURE: 175PSI. PROVIDE FLOW SWITCH WITH LINE VOLTAGE POWER.

DOMESTIC WATER ENTRY: WATTS LF909 OR EQUAL. LEAD FREE REDUCED PRESSURE ZONE ASSEMBLY. HORIZONTAL OR VERTICAL (UP OR DOWN) INSTALLATION. TEMPERATURE RANGE: 33°F - 140°F. MAXIMUM WORKING PRESSURE: 175PSI. TEMPERATURE RANGE: 33°F - 210°F. MAXIMUM WORKING PRESSURE: 175PSI (FOR MAIN SERVICE WATER ENTRY APPLICATIONS)

DOMESTIC WATER DOUBLE CHECK: WATTS LF719 OR EQUAL. LEAD FREE DOUBLE CHECK VALVE ASSEMBLY. SEPARATE ACCESS, TOP ENTRY CHECK VALVE, REVERSIBLE SEAT DISC RUBBER, VALVE TEST COCKS, TEMPERATURE RANGE: 33°F - 180°F. MAXIMUM WORKING PRESSURE: 175PSI (FOR APPLICATIONS DOWNSTREAM OF WATER ENTRY PRESSURE REDUCING VALVE)

PLUMBING SPECIFICATIONS

221613 - NATURAL GAS SYSTEMS

- NATURAL GAS PIPING ABOVE GROUND OR INSIDE BUILDINGS: SCHEDULE 40 BLACK STEEL WITH WELDED OR MALLEABLE IRON FITTINGS.
- UNDERGROUND GAS PIPE: EITHER POLYETHYLENE ASTM D2513, OR SCHEDULE 40 BLACK STEEL PRIMED AND WRAPPED IN ACCORDANCE WITH LOCAL GAS COMPANY REQUIREMENTS.
- GAS MAINS INSIDE BUILDINGS ARE SIZED FOR 2 PSIG PRESSURE. LOCATE PRESSURE REGULATORS AS SHOWN ON THE DRAWINGS TO REDUCE PRESSURE FROM 2 PSIG TO 7" W.G. PROVIDE FULL SIZE VENT LINES FROM GAS PRESSURE REGULATORS AND EXTEND TO OUTSIDE OR THROUGH ROOF. FLASH PENETRATIONS AND MAKE WATER TIGHT. INSTALL VENTLESS GAS REGULATOR AS ALTERNATE.
- PROVIDE GAS SHUT OFF VALVE AT EACH PIECE OF GAS UTILIZING EQUIPMENT.
- THE EQUIPMENT INSTALLER SHALL APPLY AND SIGN A CERTIFICATION LABEL TO EACH GAS-FIRED APPLIANCE, STATING THE APPLIANCE HAS BEEN ADJUSTED OR MODIFIED PER MANUFACTURER'S REQUIREMENTS FOR OPERATION AT THE PROJECT ALTITUDE AND WITH THE BTU-CONTENT OF THE AVAILABLE FUEL-GAS.

223000 - WATER HEATERS

- INSTALL UNITS PLUMB AND LEVEL AND FIRMLY ANCHORED PER SEISMIC REQUIREMENTS. MAINTAIN MANUFACTURER'S RECOMMENDED CLEARANCES. ORIENT SO CONTROLS AND DEVICES NEEDING SERVICING ARE ACCESSIBLE.
- CONNECT HOT AND COLD WATER PIPING TO UNITS WITH SHUT-OFF VALVES AND UNIONS. CONNECT HOT WATER CIRCULATING PIPING TO UNIT WITH SHUT-OFF VALVE, CHECK VALVE AND UNION.
- USE DIELECTRIC FITTINGS AND UNIONS WHERE PIPING CONNECTIONS ARE DISSIMILAR METALS.
- INSTALL VACUUM RELIEF VALVE IN COLD WATER INLET PIPING. EXTEND RELIEF VALVE DISCHARGE TO CLOSEST FLOOR DRAIN. INSTALL DRAIN AS INDIRECT WASTE TO SPILL INTO OPEN DRAIN OR OVER FLOOR DRAIN.
- PROVIDE AND INSTALL EXPANSION TANK AS SCHEDULED IN DRAWINGS.

EXPANSION TANK: DIAPHRAGM TYPE, PRE- PRESSURIZED STEEL TANK WITH RELIEF VALVE SETTING @ 120 PSI MAXIMUM PRESSURE.
- CONNECT GAS SUPPLY PIPING TO BURNER WITH DRIP LEG, TEE, GAS COCK, AND UNION, MINIMUM SIZE SAME AS INLET CONNECTION. INSTALL GAS PRESSURE REGULATORS WHERE INDICATED.
- CONNECT OIL PIPING TO OIL BURNER WITH SHUT-OFF VALVE AND UNION IN SUPPLY AND CHECK VALVE AND UNION IN RETURN PIPING.
- ELECTRICAL CONNECTIONS: POWER WIRING AND DISCONNECT SWITCHES ARE SPECIFIED IN DIVISION 16. CONNECT UNIT COMPONENTS TO GROUND IN ACCORDANCE WITH THE NATIONAL ELECTRICAL CODE.
- VENT CONNECTIONS: CONNECT GAS FIRED WATER HEATER DRAFT HOOD TO VENT SYSTEM, UNLESS OTHERWISE INDICATED, PROVIDE VENT SAME SIZE AS OUTLET ON HEATER. COMPLY WITH GAS UTILITY REQUIREMENTS.
- CONNECT OIL-FIRED WATER HEATER VENT AND DRAFT REGULATOR TO VENT SYSTEM. PROVIDE VENT AND DRAFT REGULATOR SAME SIZE AS OUTLET ON HEATER.
- PROVIDE SEALED COMBUSTION SYSTEMS WITH CONNECTIONS FOR OUTSIDE COMBUSTION AIR.
- PROVIDE CONCENTRIC VENT TERMINATION KIT FOR ROOF OR WALL APPLICATIONS.
- PROVIDE PVC COMBUSTION AIR AND VENT PIPING FROM WATER HEATER TO TERMINATION KIT.
- PROVIDE CONDENSATE DRAIN FROM WATER HEATER OR VENT AS REQUIRED.

PLUMBING SPECIFICATIONS

224213 - PLUMBING FIXTURES

- PROVIDE AND INSTALL CARRIERS AS REQUIRED FOR FLOOR OR WALL MOUNTED PLUMBING FIXTURES. INSTALL ALL FIXTURES WITH ACCESSORIES AS REQUIRED TO PROVIDE A COMPLETE, WORKABLE INSTALLATION.
- PLUMBING FIXTURES SHALL INCLUDE COMPRESSION STOPS ABOVE FLOOR IN SUPPLIES TO ALL FIXTURES AND A MINIMUM 17 GAUGE P-TRAP.
- ALL LAVATORIES AND HAND SINKS WILL HAVE A COMBINATION FAUCET OR PREMIXING FAUCET CAPABLE OF SUPPLYING WARM WATER FOR A MINIMUM OF 10 SECONDS.
- ALL JANITORIAL SINK FAUCETS MUST BE PROVIDED WITH AN APPROVED BACKFLOW PREVENTION DEVICE.
- FLOOR DRAINS AND FLOOR SINKS ARE SHOWN IN THE APPROXIMATE LOCATION. COORDINATE FINAL LOCATION WITH EQUIPMENT AND DRAINAGE REQUIREMENTS. PROVIDE BLOCKOUTS AS NECESSARY.

PENETRATION FIRESTOPPING NOTES

- CONTRACTOR SHALL REVIEW CONSTRUCTION DOCUMENTS AND PROVIDE SPECIFIC FIRESTOPPING DETAILS FROM A SPECIFIC FIRESTOPPING MANUFACTURER FOR EACH MECHANICAL (HVAC) AND PLUMBING PIPE OR DUCT PENETRATION FOR EACH FIRE RATED ASSEMBLY.
- PROVIDE PENETRATION FIRESTOPPING THAT IS PRODUCED AND INSTALLED TO RESIST SPREAD OF FIRE ACCORDING TO REQUIREMENTS INDICATED, RESIST PASSAGE OF SMOKE AND OTHER GASES, AND MAINTAIN ORIGINAL FIRE-RESISTANCE RATINGS OF CONSTRUCTION PENETRATED.
- PENETRATION FIRESTOPPING SYSTEMS SHALL BE COMPATIBLE WITH ONE ANOTHER, WITH THE SUBSTRATES FORMING OPENINGS, AND WITH PENETRATING ITEMS IF ANY.
- PENETRATIONS IN FIRE-RESISTANCE-RATED WALLS: PROVIDE PENETRATION FIRESTOPPING WITH RATINGS DETERMINED PER ASTM E 814 OR UL 1479, BASED ON TESTING AT A POSITIVE PRESSURE DIFFERENTIAL OF 0.01-INCH WG
- PENETRATION FIRESTOPPING PRODUCTS SHALL BEAR UL, ETL OR FM GLOBAL CLASSIFICATION MARKING OF QUALIFIED TESTING AND INSPECTING AGENCY.
- DO NOT INSTALL PENETRATION FIRESTOPPING WHEN AMBIENT OR SUBSTRATE TEMPERATURES ARE OUTSIDE LIMITS PERMITTED BY PENETRATION FIRESTOPPING MANUFACTURERS OR WHEN SUBSTRATES ARE WET BECAUSE OF RAIN, FROST, CONDENSATION, OR OTHER CAUSES.
- COORDINATE CONSTRUCTION OF OPENINGS AND PENETRATING ITEMS TO ENSURE THAT PENETRATION FIRESTOPPING IS INSTALLED ACCORDING TO SPECIFIED REQUIREMENTS.
- COORDINATE SIZING OF SLEEVES, OPENINGS, CORE-DRILLED HOLES, OR CUT OPENINGS TO ACCOMMODATE PENETRATION FIRESTOPPING.
- INSTALL PENETRATION FIRESTOPPING TO COMPLY WITH MANUFACTURER'S WRITTEN INSTALLATION INSTRUCTIONS AND PUBLISHED DRAWINGS FOR PRODUCTS AND APPLICATIONS INDICATED.
- INSTALL FORMING MATERIALS AND OTHER ACCESSORIES OF TYPES REQUIRED TO SUPPORT FILL MATERIALS DURING THEIR APPLICATION AND IN THE POSITION NEEDED TO PRODUCE CROSS-SECTIONAL SHAPES AND DEPTHS REQUIRED TO ACHIEVE FIRE RATINGS INDICATED.
- IDENTIFY PENETRATION FIRESTOPPING WITH PREPRINTED METAL OR PLASTIC LABELS. ATTACH LABELS PERMANENTLY TO SURFACES ADJACENT TO AND WITHIN 6 INCHES OF FIRESTOPPING EDGE SO LABELS WILL BE VISIBLE TO ANYONE SEEKING TO REMOVE PENETRATING ITEMS OR FIRESTOPPING.

FIRE SPRINKLER SYSTEM REQUIREMENTS (NFPA-13)

THESE DRAWINGS AND SPECIFICATIONS ARE FOR THE FIRE PROTECTION CONTRACTOR TO ENGINEER, DESIGN, BID AND INSTALL A COMPLETE AND OPERATIONAL FIRE PROTECTION SYSTEM, PER THE DESIGN INTENT AS SHOWN.

- CONTRACTOR TO PROVIDE A HYDRAULICALLY-DESIGNED, FUSIBLE LINK, FULLY SPRINKLED, WET PIPE FIRE PROTECTION SYSTEM FOR BUILDING SPACES NOT SUBJECT TO FREEZING.
- CONTRACTOR TO PROVIDE A HYDRAULICALLY-DESIGNED, FUSIBLE LINK, FULLY SPRINKLED, DRY PIPE OR GLYCOL FIRE PROTECTION SYSTEM. BUILDING SPACES SUBJECT TO FREEZING, INCLUDING PARKING GARAGES, ENTRANCE CANOPIES AND OVERHANGS.
- ALL DESIGN SHALL BE IN ACCORDANCE WITH THE LATEST ADOPTED EDITIONS OF THE BUILDING CODE, FIRE CODE, MECHANICAL CODE, PLUMBING CODE, AND ANY OTHER LOCAL, STATE OR FEDERAL REGULATIONS AND CODES, AS WELL AS INSTRUCTIONS FROM THE AUTHORITY HAVING JURISDICTION.
- SUBMIT FIRE PROTECTION LAYOUT DRAWINGS AND CALCULATIONS TO THE ENGINEER FOR GENERAL APPROVAL OF SYSTEM LAYOUT, LOCATION OF COMPONENTS ETC. THEN SUBMIT TO THE FIRE MARSHALL HAVING JURISDICTION AND OBTAIN APPROVAL. CONTRACTOR TO PAY ALL PERMIT/APPROVAL/PLAN/CHECK FEES AND COSTS INVOLVED.
- SYSTEM DESIGN SHALL BE BASED ON THE FOLLOWING CRITERIA:
 - LIGHT HAZARD IN ALL AREAS, EXCEPT ORDINARY HAZARD GROUP 1 IN THE KITCHEN AREA.
 - DESIGN THE SYSTEM USING THE AREA/DENSITY METHOD IN NFPA 13.
 - FLOW TEST DATA TO BE DETERMINED BY THE FIRE PROTECTION CONTRACTOR.
- PROVIDE COVERAGE FOR A SINGLE FIRE ZONE.
- PROVIDE INSPECTOR'S TEST CONNECTION IN A LOCATION APPROVED BY THE OWNER AND THE FIRE MARSHALL.
- DUE CONSIDERATION SHALL BE GIVEN TO THE LOCATION OF BUILDING ELEMENTS, (I.E. BEAMS, COLUMNS, LIGHT FIXTURES, ETC.) IN DETERMINING SPRINKLER HEAD SPACING AND ARRANGEMENT. THE STRUCTURE SHOWN ON ALL DETAILS MAY OR MAY NOT PERTAIN TO A PORTION OR ANY PORTION OF THE BUILDING. COORDINATE MOUNTING REQUIREMENTS WITH ARCHITECTURAL DRAWINGS AND STRUCTURAL.
- ALL EQUIPMENT, PIPING, COMPONENT, AND ACCESSORY SIZES, CAPACITIES AND TYPES SHOWN IN THESE DRAWINGS AND SPECIFICATIONS SHALL BE ADHERED TO.
- AUXILIARY DRAINS SHALL BE INCLUDED AS NECESSARY TO DRAIN ALL SPRINKLER SYSTEM DISTRIBUTION LINES AND BRANCHES DOWNSTREAM OF THE RISER CHECK VALVE.
- AUTOMATIC AIR RELEASE VALVES SHALL BE FURNISHED AS NECESSARY TO VENT THE DRY PIPE SPRINKLER SYSTEM. THE VALVES SHALL BE MADE SEPARABLE FROM THE SYSTEM WITH APPROPRIATELY SIZED GATE VALVES.
- THE CONTRACTOR SHALL THOROUGHLY TEST, DISINFECT, AND FLUSH THE PIPING SYSTEM ACCORDING TO APPLICABLE CODES AND STANDARDS.
- ANY DIMENSIONS SHOWN ARE FOR REFERENCE ONLY. CONTRACTOR SHALL VERIFY ALL DIMENSIONS AND CONNECTIONS REQUIRED FOR INSTALLATION.
- REFER TO ARCHITECTURAL DRAWINGS FOR ADDITIONAL BUILDING INFORMATION SUCH AS ATTIC SPACES, CONSTRUCTION MATERIALS, SPECIAL USE SPACES, BUILDING SECTIONS, ETC.
- SPRINKLER HEADS:
 - SPRINKLER HEADS FOR LIGHT HAZARD CLASSIFICATION SHALL BE QUICK RESPONSE TYPE PER NFPA 13. ALL OTHER CLASSIFICATIONS SHALL BE STANDARD RESPONSE TYPE.
 - GENERAL: ALL HEADS SHALL BE FACTORY MUTUAL APPROVED FOR APPLICATION AND INSTALLATION. WET OR DRY TYPE AS REQUIRED. CEILING ESCUTCHEONS MAY BE PLASTIC OR METAL 2 PIECE TYPE
 - EXPOSED HEADS IN CEILING: SEMI-RECESSED TYPE WITH SATIN CHROME-PLATED ESCUTCHEON OR CUP. WHEREVER HEADS ARE ADJACENT TO SURFACE-MOUNTED LIGHTS OR OBSTRUCTIONS, USE EXTENDED PENDENT HEAD WITH SHALLOW FRICTION ADJUSTABLE ESCUTCHEON WITH SATIN CHROME-PLATED FINISH. COORDINATE EXTENDED PENDENT HEAD USE WITH ARCHITECT PRIOR TO PURCHASE OR INSTALLATION.
- EXPOSED HEADS IN SOLID CEILINGS: SEMI-RECESSED TYPE WITH SHALLOW FRICTION ADJUSTABLE ESCUTCHEON WITH SATIN CHROME-PLATED FINISH.
- EXPOSED HEADS IN FINISHED METAL CEILING AREAS: SEMI-RECESSED TYPE WITH SATIN BRASS-PLATED ESCUTCHEON CUP, OF COLOR MATCH METAL CEILING.
- CONCEALED HEADS AND THOSE AREAS WITHOUT CEILINGS: UPRIGHT OR PENDANT TYPE WITH ROUGH BRASS FINISH.
- SPRINKLER HEADS IN ALL AREAS SHALL OPEN AT 160°-165°F, EXCEPT THAT HEADS IN BAKERY, DELI, ELECTRICAL TRANSFORMER ROOMS, AND PHONE/EMS ROOMS SHALL BE RATED AT 212°F.
- HEADS IN FREEZER/COOLER BOXES SHALL BE DRY PENDANT TYPE, AND SHALL BE OF COLOR TO MATCH CEILING.
- PENDANT HEADS ON DRY SPRINKLER SYSTEM SHALL BE DRY PENDANT TYPE AND SHALL BE OF COLOR TO MATCH CEILING.
- LEGEND:

→ UPRIGHT

● PENDENT

⦿ DRY PENDENT
- RECORD DESIGN DRAWINGS SHOWING ALL EQUIPMENT, COMPONENTS, PIPING AND CONTROLS SHALL BE PREPARED TO THE SAME SCALE AS THESE DRAWINGS. DRAWINGS SHALL BE ON MYLAR AND BE DRAWN IN AUTOCAD. DISK COPIES SHALL BE PROVIDED TO THE OWNER AND ARCHITECT/ENGINEER.
- DESIGN FOR SEISMIC DESIGN CATEGORY AND SEISMIC USE GROUP, IN ACCORDANCE WITH THE LATEST ADOPTED EDITIONS OF THE IBC, UBC, ASHRAE, AND SMACNA.
- CONTRACTOR SHALL LOCATE P.I.V., RISERS, INCOMING SERVICE, ZONE VALVES AND FEED AND BRANCH MAINS IN LOCATIONS SHOWN ON THESE DRAWINGS.
- THE WORKING DRAWINGS ARE DIAGRAMMATIC. BECAUSE OF THE SMALL SCALE OF THE DRAWINGS, THEY DO NOT SHOW EVERY OFFSET, BEND OR ELBOW NECESSARY FOR THE COMPLETE INSTALLATION IN THE SPACE PROVIDED. ALL LOCATIONS FOR FIRE PROTECTION ITEMS SHALL BE CHECKED AND COORDINATED WITH THE ARCHITECTURAL, MECHANICAL, STRUCTURAL, AND ELECTRICAL DRAWINGS.
- THE FIRE PROTECTION CONTRACTOR DOES NOT HAVE PRIORITY ON PIPE ROUTING. ALL PIPING TO BE FULLY COORDINATED WITH ALL HVAC, PLUMBING, ELECTRICAL, AND ARCHITECTURAL REQUIREMENTS AND TRADES. RESOLVE POTENTIAL CONFLICTS BEFORE PROCEEDING WITH INSTALLATION. IN ALL CASES, GRADED PIPE RUNS TAKE FIRST PRIORITY ON ROUTING. GENERALLY, DUCTWORK TAKES SECOND PRIORITY.
- UPON COMPLETION OF THE WORK, REMOVE ALL SURPLUS MATERIALS AND RUBBISH. MAKE ALL REQUIRED PATCHING AND REPAIRS OF OTHER TRADES' WORK DAMAGED BY THIS CONTRACTOR, AND LEAVE THE PREMISES IN A CLEAN, ORDERLY CONDITION.
- THE CONTRACTOR SHALL GUARANTEE THE ENTIRE FIRE PROTECTION SYSTEM FOR A PERIOD OF ONE YEAR FROM THE DATE OF SUBSTANTIAL COMPLETION.
- ALL ALLOWABLE SPRINKLER SYSTEM COMPONENTS SHALL BE PRIMED AND PAINTED RED, SYSTEM COMPONENTS WHICH MAY BE INACCESSIBLE AFTER INSTALLATION SHALL BE PAINTED BEFORE INSTALLATION.
- IN AREAS WITH LAY-IN CEILINGS. LOCATE HEADS IN THE CENTER OF THE CEILING TILE. PROVIDE ALL NECESSARY ELBOWS IN BRANCH LINES, TO ACHIEVE THIS.

Donald L. Welch

Architect

7533 Sandy Land Lane
Midvale, Utah 84047
801.548-6391
dwelch5977@msn.com




324 S. State St., Suite 400
Salt Lake City, UT 84111
801-328-5151
801-678-7077
fax: 801-328-5155
www.spectrum-engineers.com

THE DESIGNS SHOWN AND DESCRIBED HEREIN INCLUDING ALL TECHNICAL DRAWINGS, GRAPHIC REPRESENTATION & MODELS THEREOF, ARE PROPRIETARY & CAN NOT BE COPIED, DUPLICATED, OR COMMERCIALLY EXPLOITED IN WHOLE OR IN PART WITHOUT THE SOLE AND EXPRESS WRITTEN PERMISSION FROM DONALD L. WELCH ARCHITECT

THESE DRAWINGS ARE AVAILABLE FOR LIMITED REVIEW AND EVALUATION BY CLIENTS CONSULTANTS, CONTRACTORS, GOVERNMENT AGENCIES, VENDORS, AND OFFICE PERSONNEL ONLY IN ACCORDANCE WITH THIS NOTICE.

consultant:



project:

Tenant Finish
for New
Brighton
Recovery
Campus
4905, 4911, 4915,
4925, 4931, & 4953
South 900 East
Salt Lake County,
Utah

date

April 24, 2017

revisions

PERMIT SET--December 28, 2016
Δ ADDENDUM #1--January 04, 2017
Δ ADDENDUM #3--January 11, 2017
Δ ADDENDUM #4--January 17, 2017
Δ ADDENDUM #5--January 20, 2017
Δ ADDENDUM #7--February 24, 2017
Δ ADDENDUM #8 -- March 20, 2017
Δ ADDENDUM #9 -- April 11, 2017

data

project no:

draw by:

checked by:

title

PLUMBING
EQUIPMENT
SPECIFICATIONS
sheet

P02

BUILDING 'D'




324 S. State St., Suite 400
Salt Lake City, UT 84111
800-678-7077
801-328-5151
fax: 801-328-5155
www.spectrum-engineers.com

THE DESIGNS SHOWN AND DESCRIBED HEREIN INCLUDING ALL TECHNICAL DRAWINGS, GRAPHIC REPRESENTATION & MODELS THEREOF, ARE PROPRIETARY & CAN NOT BE COPIED, DUPLICATED, OR COMMERCIALY EXPLOITED IN WHOLE OR IN PART WITHOUT THE SOLE AND EXPRESS WRITTEN PERMISSION FROM DONALD L. WELCH ARCHITECT

THESE DRAWINGS ARE AVAILABLE FOR LIMITED REVIEW AND EVALUATION BY CLIENTS, CONSULTANTS, CONTRACTORS, GOVERNMENT AGENCIES, VENDORS, AND OFFICE PERSONNEL ONLY IN ACCORDANCE WITH THIS NOTICE.

consultant:



project:

Tenant Finish
for New
Brighton
Recovery
Campus
4905, 4911, 4915,
4925, 4931, & 4953
South 900 East
Salt Lake County,
Utah

date

April 24, 2017

revisions

- PERMIT SET-December 28, 2016
ADDENDUM #1-January 04, 2017
ADDENDUM #3-January 11, 2017
ADDENDUM #4-January 17, 2017
ADDENDUM #5-January 20, 2017
ADDENDUM#7-February 24, 2017
ADDENDUM#8 - March 20, 2017
ADDENDUM#9 - April 11, 2017

data

project no:

drawn by:

checked by:

title


PLUMBING
SCHEDULES &
DETAILS
sheet

P11

BUILDING 'D'

PLUMBING FIXTURE SCHEDULE (COORDINATE MOUNTING HEIGHTS WITH ARCH. PLANS)


SYMBOL	FIXTURE	MANUFACTURER AND MODEL NO.	COLD WATER	HOT WATER	WASTE	VENT	ACCESSORIES AND REMARKS
FD-1 FD-2	FLOOR DRAINS	SEE P02 (SPEC SECTION 221316)	-	-	2" OR 4"	1-1/2" OR 3"	REFERENCE SHEET P02. FLOOR DRAINS IN FINISHED SPACES TO BE FD-1 (2"). ALL WATER ENTRY DRAINS TO BE FD-2 (4"). INSTALL PROVENT TRAP GUARD OR EQUAL IN EACH DRAIN TYPE.
FIRE & DOMESTIC WATER ENTRIES DOUBLE CHECK & BACKFLOW DEVICES			SEE P02 (SPEC SECTION 221316)	SEE REMARKS	-	-	REFERENCE SHEET P02. MAKE/MODELS FOR FIRE/WATER ENTRY BACKFLOW PREVENTER AND DOUBLE CHECK DETECTOR ASSEMBLIES INDICATED. 4" FIRE ENTRY LINE WHERE INDICATED. BUILDINGS C & D TO INCORPORATE A 1-1/2" WATER SERVICE. BUILDINGS A, B, E, F TO HAVE 2" DOMESTIC WATER SERVICE. LOCATE FIRE CONTROL PANEL AT EACH FIRE ENTRY. <u>ELECTRICAL:</u> PROVIDE LINE VOLTAGE POWER (115V CIRCUITS) TO FIRE ENTRY FLOW SWITCH & AIR COMPRESSOR
SH-1	SHOWER (ADA) (FLOOR MOUNTED)	SEE ARCHITECTURAL	1/2"	1/2"	2"	1-1/2"	REFERENCE ARCHITECTURAL SHEET A6.1A. SPECIFICATIONS FOR SHOWER INSERT, DRAIN, SHOWERHEAD, VALVES, & ASSOCIATED ACCESSORIES ARE INDICATED.
GWH-1	GAS WATER HEATER (FLOOR MOUNTED)	BRADFORD WHITE EF-100T-300E-3N(A)	1-1/2"	1-1/2"	-	-	COMMERCIAL ULTRA HIGH EFFICIENCY GAS WATER HEATER. 92% THERMAL EFFICIENCY. DIRECT SPARK IGNITION. 300 MBH INPUT. 3/4" GAS CONNECTION. 100 GALLON CAPACITY. 335 GPH RECOVERY @ 100°F. DISCHARGE T&P VALVE INTO MOP SINK OR FLOOR DRAIN. PROVIDE 4.4 GALLON EXPANSION TANK (AMTROL EX-30 OR EQUAL). PROVIDE SEISMIC WATER HEATER STRAPS. DIMENSIONS: 77-5/8" H X 28-1/4" DIA. 900 LB SHIPPING WEIGHT. PROVIDE 4" (PVC, CPVC, OR ABS) VERTICAL VENTING. TERMINATE THROUGH ROOF WITH CONCENTRIC VENT KIT PER MANUFACTURER'S RECOMMENDATIONS. <u>ELECTRICAL:</u> 115V AC REQUIRED.
GWH-2	GAS WATER HEATER (FLOOR MOUNTED)	BRADFORD WHITE EF-100T-250E-3N(A)	1-1/2"	1-1/2"	-	-	COMMERCIAL ULTRA HIGH EFFICIENCY GAS WATER HEATER. 97% THERMAL EFFICIENCY. DIRECT SPARK IGNITION. 250 MBH INPUT. 3/4" GAS CONNECTION. 100 GALLON CAPACITY. 294 GPH RECOVERY @ 100°F. DISCHARGE T&P VALVE INTO MOP SINK OR FLOOR DRAIN. PROVIDE 4.4 GALLON EXPANSION TANK (AMTROL EX-30 OR EQUAL). PROVIDE SEISMIC WATER HEATER STRAPS. DIMENSIONS: 77-5/8" H X 28-1/4" DIA. 900 LB SHIPPING WEIGHT. PROVIDE 4" (PVC, CPVC, OR ABS) VERTICAL VENTING. TERMINATE THROUGH ROOF WITH CONCENTRIC VENT KIT PER MANUFACTURER'S RECOMMENDATIONS. <u>ELECTRICAL:</u> 115V AC REQUIRED.
GWH-3	GAS WATER HEATER (FLOOR MOUNTED)	BRADFORD WHITE LG2PDV50H603N	3/4"	3/4"	-	-	LIGHT DUTY COMMERCIAL POWER DIRECT VENT GAS WATER HEATER. 60 MBH INPUT. 1/2" GAS CONNECTION. 48 GALLON CAPACITY. 58 GPH RECOVERY @ 100°F. DISCHARGE T&P VALVE INTO MOP SINK OR FLOOR DRAIN. PROVIDE 2.1 GALLON EXPANSION TANK (WATTS PLT-5 OR EQUAL). PROVIDE SEISMIC WATER HEATER STRAPS. DIMENSIONS: 67" H X 22" DIA. 205 LB SHIPPING WEIGHT. PROVIDE 3" (PVC, CPVC, OR ABS) VERTICAL VENTING. TERMINATE THROUGH ROOF WITH CONCENTRIC VENT KIT PER MANUFACTURER'S RECOMMENDATIONS. <u>ELECTRICAL:</u> 110 VAC REQUIRED FOR POWER VENTING (3.1 AMPERES)
GWH-4	GAS WATER HEATER (FLOOR MOUNTED)	BRADFORD WHITE EF-60T-199E-3N(A)	1-1/2"	1-1/2"	-	-	COMMERCIAL ULTRA HIGH EFFICIENCY GAS WATER HEATER. 92% THERMAL EFFICIENCY. DIRECT SPARK IGNITION. 199 MBH INPUT. 3/4" GAS CONNECTION. 60 GALLON CAPACITY. 223 GPH RECOVERY @ 100°F. DISCHARGE T&P VALVE INTO MOP SINK OR FLOOR DRAIN. PROVIDE 4.4 GALLON EXPANSION TANK (AMTROL EX-30 OR EQUAL). PROVIDE SEISMIC WATER HEATER STRAPS. DIMENSIONS: 67" H X 22" DIA. 205 LB SHIPPING WEIGHT. PROVIDE 3" (PVC, CPVC, OR ABS) VERTICAL VENTING. TERMINATE THROUGH ROOF WITH CONCENTRIC VENT KIT PER MANUFACTURER'S RECOMMENDATIONS. <u>ELECTRICAL:</u> 115V AC REQUIRED.
HWCP-1	HOT WATER CIRCULATION PUMP	GRUNDFOS UP10-16BN5/TLC	-	1/2"	-	-	RECIRCULATION PUMP WITH MANUAL TIMER TO ALLOW FOR OPERATION DURING BUSINESS HOURS. INTEGRAL CHECK VALVE. <u>ELECTRICAL:</u> 115V PLUG IN TYPE. (6 FT LINE CORD)
HWCP-2	HOT WATER CIRCULATION PUMP	GRUNDFOS UP25-64SF	-	1/2"	-	-	RECIRCULATION PUMP. INTEGRAL CHECK VALVE. 5 GPM @ 15 FT HEAD, INTEGRAL CHECK VALVE. <u>ELECTRICAL:</u> 115V PLUG IN TYPE. (6 FT LINE CORD) 1/12 HP, 1.7 AMPS
MSB-1	MOP SINK BASIN	FLORESTONE MSR-2424	3/4"	3/4"	3"	1-1/2"	MOLDED MOP RECEPTOR. 24X24, 10" DEPTH. 18 GAUGE SS DRAIN GRID (#430). KOHLER K-8928. SERVICE SINK FAUCET, 3" THREADED THREADED SPOUT FOR HOSE CONNECTION, RUBBER HOSE WITH WALL HOOK. LEVER HANDLES
FS-1	FLOOR SINK	ZURN FD2375 (OR APPROVED EQUAL)	-	-	3"	1-1/2"	ENAMELED CAST IRON, ACID RESISTANT, DOME STRAINER, FULL GRATE
WM-1 WM-2	WATER METER (SUB-METERING)	BADGER RECORDALL MODEL M120 & M170 (OR APPROVED EQUAL)	-	1-1/2" 2"	-	-	LEAD FREE BRONZE ALLOW DISC METER (MATCH BUILDING WATER ENTRY SIZE 1-1/2" OR 2"), COMPLIES WITH AWWA STANDARD C700. 150 PSI MAX OPERATING PRESSURE.
BFP-1	BACKFLOW PREVENTER	WATTS MODEL SD-2 (OR APPROVED EQUAL)	1/2"	-	-	-	BACKFLOW PREVENTER FOR CARBONATED BEVERAGE MACHINES. DUAL CHECK DESIGN FOR PROTECTION OF WATER SUPPLY FROM CARBON DIOXIDE GAS AND CARBONATED WATER. ANSISNF STD 18 CERTIFIED, ASSE 1032 APPROVED DUAL CHECK VALVE. 316 STAINLESS STEEL BODY. MAX PRESSURE: 200 PSI, MAX TEMP: 110°F. PROVIDE RECOMMENDED STRAINER.
GD-1	FOOD WASTE DISPOSER	INSINKERATOR EVOLUTION	-	-	1-1/2"	-	ANTI-VIBRATION MOUNT, 34.6 OZ. CAPACITY, 12-1/4" HEIGHT. <u>ELECTRICAL:</u> 120 V, 3/4 HP, 8.1 AMPS
KS-1	KITCHEN SINK & FAUCET:	KOHLER K-3996-4 & KOHLER FORTE K-10445	1/2"	1/2"	1-1/2"	1-1/2"	33X22X6 DUAL BOWL TOP-MOUNT ADA SINK, 4 HOLE, 18 GAUGE SS, 4" FAUCET CENTERS, 18 GAUGE SS, FAUCET: PULL-OUT SPRAY, 1.8 GPM, LEVER HANDLES, (ADA), 7-3/4" SPOUT REACH, 4 HOLES.
UR-1 UR-2	URINAL (ADA)	SLOAN SU-1006 & ROYAL 181	1"	-	1-1/2"	1-1/2"	TOP SPUD WALL HUNG, STANDARD WASHDOWN URINAL, VITREOUS CHINA 1.5 GPF MANUAL FLUSHOMETER WITH WATER HAMMER ARRESTOR.
WC-1 WC-2	WATER CLOSET, FLOOR MOUNT (ADA)	SLOAN WETS-2450.1301 & ROYAL 113-1.28	1-1/2"	-	4"	2"	VITREOUS CHINA, ELONGATED BOWL, 1-1/2" TOP SPUD, COMMERCIAL TOILET SEAT, & BOLT CAP ACCESSORY 1.28 GPF MANUAL FLUSHOMETER. PROVIDE WITH WATER HAMMER ARRESTOR.
L-1	LAVATORY (ADA) FAUCET:	SLOAN SS-3001 & KOHLER K-16027-4	1/2"	1/2"	1-1/2"	1-1/2"	19.5"X16.5" VITREOUS CHINA UNDERMOUNTED WITH OVERFLOW. SINGLE HOLE BATHROOM FAUCET (ADA) LESS POP-UP TAIL PIECE. 1.2 GPM. 4-3/8" REACH. PROVIDE BDT VARIATION BELOW DECK THERMOSTATIC MIXING VALVE (SET WATER TEMP TO 110°F) PROVIDE UNDERCOUNTER PIPING INSULATION KIT.
L-2	LAVATORY (ADA) FAUCET:	SLOAN SS-3101 & KOHLER K-16027-4	1/2"	1/2"	2"	1-1/2"	20 3/4"X18 1/4" VITREOUS CHINA WALL MOUNTED LAVATORY. SINGLE HOLE. SINGLE HOLE BATHROOM FAUCET (ADA) LESS POP-UP TAIL PIECE. 1.2 GPM. 4-3/8" REACH. PROVIDE BDT VARIATION BELOW DECK THERMOSTATIC MIXING VALVE (SET WATER TEMP TO 110°F) PROVIDE UNDERCOUNTER PIPING INSULATION KIT.
S-1	SINK FAUCET:	KOHLER VAULT K-5286 UNDER-MOUNT KITCHEN SINK	1/2"	1/2"	1-1/2"	1-1/2"	24"X18-1/4" 16-GAUGE STAINLESS STEEL, SINGLE SQUARED BOWL, 9-INCH DEPTH FAUCET: KOHLER CORALAIS KITCHEN SINK FAUCET MODEL K-15888-K WRISTBLADE LEVER HANDLED FAUCET (ADA), 9" GOOSENECK SWING SPOUT. 1.8 GPM
S-2	SINK (ADA) FAUCET:	KOHLER VAULT K-3349-2 TOP MOUNT SINK	1/2"	1/2"	1-1/2"	1-1/2"	15"X15" 19-GAUGE STAINLESS STEEL, SINGLE BOWL, 2 FAUCET HOLES. 7-9/16-INCH DEPTH FAUCET: KOHLER CORALAIS KITCHEN SINK FAUCET MODEL K-15888-K WRISTBLADE LEVER HANDLED FAUCET (ADA), 9" GOOSENECK SWING SPOUT. 1.8 GPM
DF-1	DRINKING FOUNTAIN	ELKAY ECDFPW314C	1/2"	-	2"	1-1/2"	ADA HEIGHT DRINKING FOUNTAIN, WALL MOUNT, FULLY EXPOSED. 304 STAINLESS STEEL WITH SATIN FINISH.
EW-1	ELECTRIC WATER COOLER	ELKAY LZWS-LRPBM28K	1/2"	-	2"	1-1/2"	DUAL HEIGHT WATER COOLER WITH FILTER WITH INTEGRAL SENSOR ACTIVATED 1.1 GPM BOTTLE FILLING STATION. STAINLESS STEEL. 8 GPH. RECIPROCATING TYPE COOLING SYSTEM. ELECTRICAL: 115V, 370 WATTS, 5.0 FLA (INSTALLATION REQUIRES 12" WALL DEPTH)
NOTES: 1. ALL FIXTURE FINISHES TO BE REVIEWED BY ARCHITECT PRIOR TO ORDERING. 2. PROVIDE WATER HAMMER ARRESTORS @ ALL ICE MACHINES, WASHING MACHINES, & DISHWASHERS.							




1

PLUMBING SCHEMATIC


SCALE: NTS




7 WALL CLEAN OUT
SCALE: NTS




8 WATER HEATER DETAIL
SCALE: NTS




9 CONDENSATE DRAIN DETAIL
SCALE: NTS




4 FLOOR DRAIN DETAIL
SCALE: NTS




5 CLEANOUT TO GRADE
SCALE: NTS




6 FLOOR CLEANOUT
SCALE: NTS



1 COLD WATER SERVICE ANCHORING
SCALE: NTS



2 PIPE HANGER
SCALE: NTS



3 WATER ENTRY DETAIL
SCALE: NTS

Donald L. Welch
Architect
7533 Sandy Land Lane
Midvale, Utah 84047
801.548-6391
dwelch5977@msn.com




324 S. State St., Suite 400
Salt Lake City, UT 84111
800-678-7077
801-328-5151
fax: 801-328-5155
www.spectrum-engineers.com

THE DESIGNS SHOWN AND DESCRIBED HEREIN INCLUDING ALL TECHNICAL DRAWINGS, GRAPHIC REPRESENTATION & MODELS THEREOF, ARE PROPRIETARY & CAN NOT BE COPIED, DUPLICATED, OR COMMERCIALY EXPLOITED IN WHOLE OR IN PART WITHOUT THE SOLE AND EXPRESS WRITTEN PERMISSION FROM DONALD L. WELCH ARCHITECT

THESE DRAWINGS ARE AVAILABLE FOR LIMITED REVIEW AND EVALUATION BY CLIENTS, CONSULTANTS, CONTRACTORS, GOVERNMENT AGENCIES, VENDORS, AND OFFICE PERSONNEL ONLY IN ACCORDANCE WITH THIS NOTICE.

consultant:



project:

Tenant Finish
for New
Brighton
Recovery
Campus
4905, 4911, 4915,
4925, 4931, & 4953
South 900 East
Salt Lake County,
Utah

date

April 24, 2017

revisions

- PERMIT SET-December 28, 2016
- ADDENDUM #1-January 04, 2017
- ADDENDUM #3-January 11, 2017
- ADDENDUM #4-January 17, 2017
- ADDENDUM #5-January 20, 2017
- ADDENDUM#7-February 24, 2017
- ADDENDUM#8 - March 20, 2017
- ADDENDUM#9 - April 11, 2017

data


project no:
drawn by:
checked by:

title
PLUMBING
DETAILS


sheet

P12


BUILDING 'D'




5 FIRE SPRINKLER ENTRY DETAIL
SCALE: NOT TO SCALE




4 DRY PIPE FIRE SPRINKLER AIR COMPRESSOR DETAIL
SCALE: NOT TO SCALE




1 VENT THRU ROOF DETAIL
SCALE: NTS




DOMESTIC REDUCED PRESSURE BACKFLOW PREVENTER



FIRE VERTICAL BACKFLOW PREVENTER



2 FLOOR SINK DETAIL
SCALE: NTS



3 3-COMPARTMENT SINK DETAIL
SCALE: NTS
NOTE: PROVIDE HOT WATER CIRCULATION LINE AS NOTED ON PLAN VIEW. DISHWASHER TO DRAIN INTO FLOOR SINK BELOW 3-COMP SINK.

6 BACKFLOW PREVENTION DETAILS
SCALE: NOT TO SCALE

Donald L. Welch
Architect
7533 Sandy Land Lane
Midvale, Utah 84047
801.548-6391
dwelch5977@msn.com




324 S. State St., Suite 400
Salt Lake City, UT 84111
800-678-7077
801-328-5151
fax: 801-328-5155
www.spectrum-engineers.com

THE DESIGNS SHOWN AND DESCRIBED HEREIN INCLUDING ALL TECHNICAL DRAWINGS, GRAPHIC REPRESENTATION & MODELS THEREOF, ARE PROPRIETARY & CAN NOT BE COPIED, DUPLICATED, OR COMMERCIALY EXPLOITED IN WHOLE OR IN PART WITHOUT THE SOLE AND EXPRESS WRITTEN PERMISSION FROM DONALD L. WELCH ARCHITECT

THESE DRAWINGS ARE AVAILABLE FOR LIMITED REVIEW AND EVALUATION BY CLIENTS CONSULTANTS, CONTRACTORS, GOVERNMENT AGENCIES, VENDORS, AND OFFICE PERSONNEL ONLY IN ACCORDANCE WITH THIS NOTICE.

consultant:



project:

Tenant Finish
for New
Brighton
Recovery
Campus
4905, 4911, 4915,
4925, 4931, & 4953
South 900 East
Salt Lake County,
Utah

date

April 24, 2017

revisions

- PERMIT SET-December 28, 2016
- ADDENDUM #1-January 04, 2017
- ADDENDUM #3-January 11, 2017
- ADDENDUM #4-January 17, 2017
- ADDENDUM #5-January 20, 2017
- ADDENDUM#7-February 24, 2017
- ADDENDUM#8 - March 20, 2017
- ADDENDUM#9 - April 11, 2017

data

project no:

drawn by:

checked by:

title

PLUMBING

DETAILS


sheet

P13

BUILDING 'D'

Equipment Schedule


ItemNo	Quantity	Category	Mfr	Model	Cold Water (in)	Cold Water Conn. Height(in)	Hot Water (in)	Hot Water Conn. Height(in)	Indirect Waste Size	Direct Waste Size	Direct Waste Conn. Height(in)
K-01	1	Reach-In Refrigerator	Beverage Air	HRP2-1S							
K-02	1	Reach-In Freezer	Beverage Air	FB23-1S							
K-03	1	Shelving - Sizing TBD	Custom	SHELVING							
K-04	1	Work Table	Eagle Group	BPT-2436KL-X							
K-05	1	Nugget Ice Maker	Scotsman	N0422A-1	3/8"				3/4"		
K-06	1	Work Table	Eagle Group	T3648B							
K-06	1	Work Table	Eagle Group	T3660EB-B5							
K-07	1	Espresso Cappuccino Machine	Rancilio/Egro	EPOCA S1							
K-08	1	Soft Serve Machine	ElectroFreeze	CS8							
K-09	1	Mega Top Sandwich / Salad Preparation Refrigerator	Beverage Air	SPE48-18M							
K-10	2	Work Table	Eagle Group	BPT-3060FL-X							
K-11		Spare Number									
K-12	1	Dishwasher, Undercounter	Jackson WWS	AVENGER HT-E			1/2"		1-3/8"		
K-13	2	Shelving, Wall-Mounted	Eagle Group	WS1236-16/4							
K-14	1	Three (3) Compartment Sink	Eagle Group	BPS-1854-3-18L-FC-X							
	1		T&S Brass	B-0133-CCB	1/2"		1/2"				
K-15		Spare Number									
K-16	1	Hand Sink	Eagle Group	HSA-10-F-1X						1-1/2"	
K-17	1	Hood #1	Captive Aire	HOOD #1							
K-18	1	Range, 60", 6 Burners, 24" Griddle	Imperial	IR-6-G24							



STANDARD
Restaurant Supply

Terrill Roe
Restaurant Sales
Design Consultant
801-834-8896
terrill@standardrestaurant.com

3500 S West Temple
Salt Lake City, Utah 84115



FLOOR PLAN

Date
20161229

Project
03-231

Project Name
Brighton Recovery - Plumbing

K-04

ALL RIGHTS RESERVED. Terrill J. Roe. COPYRIGHT
This drawing is intended as a guide only and is not to be used for construction without the approval of the architect. The architect is not responsible for the accuracy of the information provided in this drawing. The architect is not responsible for the accuracy of the information provided in this drawing. The architect is not responsible for the accuracy of the information provided in this drawing.

Donald L. Welch
Architect
7533 Sandy Land Lane
Midvale, Utah 84047
801.548-6391
dwelch5977@msn.com




324 S. State St., Suite 400
Salt Lake City, UT 84111
801-678-7077
801-328-5151
fax: 801-328-5155
www.spectrum-engineers.com

THE DESIGNS SHOWN AND DESCRIBED HEREIN INCLUDING ALL TECHNICAL DRAWINGS, GRAPHIC REPRESENTATION & MODELS THEREOF, ARE PROPRIETARY & CAN NOT BE COPIED, DUPLICATED, OR COMMERCIALY EXPLOITED IN WHOLE OR IN PART WITHOUT THE SOLE AND EXPRESS WRITTEN PERMISSION FROM DONALD L. WELCH ARCHITECT.

THESE DRAWINGS ARE AVAILABLE FOR LIMITED REVIEW AND EVALUATION BY CLIENTS, CONSULTANTS, CONTRACTORS, GOVERNMENT AGENCIES, VENDORS, AND OFFICE PERSONNEL ONLY IN ACCORDANCE WITH THIS NOTICE.

consultant:



project:

Tenant Finish
for New
Brighton
Recovery
Campus
4905, 4911, 4915,
4925, 4931, & 4953
South 900 East
Salt Lake County,
Utah

date

April 24, 2017

revisions

- PERMIT SET-December 28, 2016
- ADDENDUM #1-January 04, 2017
- ADDENDUM #3-January 11, 2017
- ADDENDUM #4-January 17, 2017
- ADDENDUM #5-January 20, 2017
- ADDENDUM#7-February 24, 2017
- ADDENDUM#8 - March 20, 2017
- ADDENDUM#9 - April 11, 2017


data

project no:
drawn by:
checked by:

title
PLUMBING
DETAILS

sheet

P14
BUILDING 'D'



KEYED NOTES

- MECHANICAL
- M1 LOCATION OF NEW ROOFTOP UNIT. COORDINATION FINAL LOCATION WITH EXISTING STRUCTURE. PROVIDE FLEXIBLE CONNECTION ON SUPPLY AND RETURN DUCTWORK TO MINIMIZE VIBRATION. PROVIDE EQUIPMENT CURB WITH RTU.
- M2 LOCATION OF ROOF ACCESS HATCH. HORIZONTAL ACCESS PATH TO SIDEWALL OF EXISTING EQUIPMENT WELL WITHIN ATTIC SPACE TO BE PROVIDED WHERE MAIN LEVEL CEILING ACCESS PANEL IS NOT LOCATED DIRECTLY BELOW EQUIPMENT WELL. REFERENCE ARCHITECTURAL PLANS FOR INSTALLATION DETAILS AND DIMENSIONS.
- PLUMBING
- P1 ROUTE NEW GAS LINE TO UNDERSIDE OF ROOFTOP UNIT. PROVIDE GAS PRESSURE REGULATOR AND ISOLATION VALVE PER MANUFACTURER'S RECOMMENDATIONS.

GENERAL NOTES


1. PROVIDE NECESSARY EQUIPMENT CURBS/PLATFORMS FOR ALL EXTERIOR MECHANICAL EQUIPMENT.
2. EXISTING PRIMARY AND OVERFLOW ROOF DRAINS TO REMAIN. COORDINATE LOCATIONS OF ROOFTOP UNITS ACCORDINGLY. REPLACE DAMAGED ROOF DRAINS AS REQUIRED.
3. PROVIDE NECESSARY CLEARANCES TO ALLOW FOR SERVICE TO ALL ROOFTOP EQUIPMENT. COORDINATE RTU LOCATIONS WITH ROOF ACCESS HATCHES.
4. ALL GAS PIPING SIZED PER TABLE 402.4(2) 2015 IFGC. GAS PRESSURE DOWNSTREAM OF METER IS LESS THAN 2 PSI.
5. EXISTING VENT-THRU-ROOF LOCATIONS TO BE REUSED WHERE POSSIBLE. PROVIDE NEW VERTICAL VENT EXTENSIONS AS REQUIRED.
6. ROUTE CONDENSATE LINES FROM RTUS TO NEARBY EXISTING ROOF DRAIN. PROVIDE FULL SIZE DRAIN LINE AND TRAP PER MANUFACTURER'S RECOMMENDATIONS.
7. PROVIDE 10 FEET SEPARATION DISTANCE BETWEEN ALL RTU OUTSIDE AIR INTAKE LOCATIONS AND PLUMBING VENT TERMINATIONS.

SERVICE PLATFORM NOTES

1. EVERY OPEN-SIDED FLOOR OR PLATFORM 4 FEET OR MORE ABOVE ADJACENT FLOOR OR GROUND LEVEL SHALL BE GUARDED BY A STANDARD RAILING ON ALL OPEN SIDES EXCEPT WHERE THERE IS ENTRANCE TO A RAMP, STAIRWAY, OR FIXED LADDER. THE RAILING SHALL BE PROVIDED WITH A TOEBOARD WHEREVER, BENEATH THE OPEN SIDES, PERSONS CAN PASS, THERE IS MOVING MACHINERY, OR THERE IS EQUIPMENT WITH WHICH FALLING MATERIALS COULD CREATE A HAZARD.
2. A STANDARD RAILING SHALL CONSIST OF TOP RAIL, INTERMEDIATE RAIL, AND POSTS, AND SHALL HAVE A VERTICAL HEIGHT OF 42 INCHES NOMINAL FROM UPPER SURFACE OF TOP RAIL TO FLOOR, PLATFORM, RUNWAY, OR RAMP LEVEL. THE TOP RAIL SHALL BE SMOOTH-SURFACED THROUGHOUT THE LENGTH OF THE RAILING. THE INTERMEDIATE RAIL SHALL BE APPROXIMATELY HALFWAY BETWEEN THE TOP RAIL AND THE FLOOR, PLATFORM, RUNWAY, OR RAMP. THE ENDS OF THE RAILS SHALL NOT OVERHANG THE TERMINAL POSTS EXCEPT WHERE SUCH OVERHANG DOES NOT CONSTITUTE A PROJECTION HAZARD.
3. A STANDARD TOEBOARD SHALL BE 4 INCHES NOMINAL IN VERTICAL HEIGHT FROM ITS TOP EDGE TO THE LEVEL OF THE FLOOR, PLATFORM, RUNWAY, OR RAMP. IT SHALL BE SECURELY FASTENED IN PLACE AND WITH NOT MORE THAN 1/4-INCH CLEARANCE ABOVE FLOOR LEVEL. IT MAY BE MADE OF ANY SUBSTANTIAL MATERIAL EITHER SOLID OR WITH OPENINGS NOT OVER 1 INCH IN GREATEST DIMENSION. WHERE MATERIAL IS PILED TO SUCH HEIGHT THAT A STANDARD TOEBOARD DOES NOT PROVIDE PROTECTION, PANELING FROM FLOOR TO INTERMEDIATE RAIL, OR TO TOP RAIL SHALL BE PROVIDED.
4. CONSTRUCTION TO BE OF 16G MATERIAL (MIN.) WALKING SURFACE TO BE GRATED MATERIAL TO ALLOW FOR DRAINAGE.
5. GENERAL CONTRACTOR TO PROVIDE SHOP DRAWING OF WORKING PLATFORM FOR APPROVAL BY OWNER & ARCHITECT.

MECH/PLUMB ROOF PLAN-BUILDING 'D'

SCALE: 1/4" = 1'-0"



Donald L. Welch
Architect
7533 Sandy Land Lane
Midvale, Utah 84047
801.548-6391
dwelch5977@msn.com




324 S. State St., Suite 400
Salt Lake City, UT 84111
800-678-7077
801-328-5151
fax: 801-328-5155
www.spectrum-engineers.com

THE DESIGNS SHOWN AND DESCRIBED HEREIN INCLUDING ALL TECHNICAL DRAWINGS, GRAPHIC REPRESENTATION & MODELS THEREOF, ARE PROPRIETARY & CAN NOT BE COPIED, DUPLICATED, OR COMMERCIALY EXPLOITED IN WHOLE OR IN PART WITHOUT THE SOLE AND EXPRESS WRITTEN PERMISSION FROM DONALD L. WELCH ARCHITECT

THESE DRAWINGS ARE AVAILABLE FOR LIMITED REVIEW AND EVALUATION BY CLIENTS CONSULTANTS, CONTRACTORS, GOVERNMENT AGENCIES, VENDORS, AND OFFICE PERSONNEL ONLY IN ACCORDANCE WITH THIS NOTICE.

consultant:



project:

Tenant Finish
for New
Brighton
Recovery
Campus
4905, 4911, 4915,
4925, 4931, & 4953
South 900 East
Salt Lake County,
Utah

date

April 24, 2017

revisions

- PERMIT SET-December 28, 2016
- ADDENDUM #1-January 04, 2017
- ADDENDUM #3-January 11, 2017
- ADDENDUM #4-January 17, 2017
- ADDENDUM #5-January 20, 2017
- ADDENDUM#7-February 24, 2017
- ADDENDUM#8 - March 20, 2017
- ADDENDUM#9 - April 11, 2017

data

project no:

drawn by:

checked by:

title

MECH/PLUMB
ROOF PLAN
BUILDING 'D'
sheet

MP1D

BUILDING 'D'

KEYED NOTES

- M1 INSTALL EXHAUST FAN AT THIS LOCATION. CONTINUE EXHAUST DUCT TO TERMINATE AT UNDERSIDE OF BUILDING OVERHANG AS INDICATED. COORDINATE LOCATION WITH OVERHEAD PLUMBING.
- M2 SEE ROOF PLAN FOR CONTINUATION OF SUPPLY AND RETURN AIR DUCTWORK.
- M3 LOCATION OF RECESSED DRYER VENT BOX. CONTINUE 4" DRYER DUCT TO TERMINATE AT UNDERSIDE OF BUILDING OVERHANG AS INDICATED.
- M4 RE-CIRCULATING KITCHEN HOOD.
- M5 PROVIDE TERMINATION KIT FOR DRYER EXHAUST AT THIS LOCATION.
- M6 LOCATION FOR DIGITAL THERMOSTAT WITHIN LOCKING ENCLOSURE.
- M7 ACCESS PANEL TO ALLOW FOR ADJUSTMENT TO ABOVE CEILING BALANCING DAMPER.
- M8 LOCATE OUTDOOR CONDENSING UNIT AS REQUIRED. PROVIDE CONCRETE EQUIPMENT PAD AS NECESSARY. SEE EQUIPMENT SCHEDULE FOR NECESSARY ACCESSORIES. CONCEAL ALL REFRIGERANT PIPING.

GENERAL NOTES


1. PROVIDE BALANCING DAMPERS ON ALL GRILLES, REGISTERS, & DIFFUSERS CONNECTED TO A ROOFTOP UNIT. ALLOW FOR ADJUSTMENT BY REMOVAL OF EXHAUST GRILLES OR BY PROVIDING ACCESS PANELS. (TYPICAL)
2. ROUTE SUPPLY AND RETURN AIR DUCTWORK THROUGH STRUCTURE AS REQUIRED. PROVIDE NECESSARY TRANSITIONS TO ALLOW FOR CLEAN PATH THE TERMINAL AIR DEVICES.
3. PROVIDE WATER TIGHT SEAL ON ALL DUCTWORK AS IT PENETRATE EXTERIOR ROOFING/WALL ASSEMBLIES.
4. PROVIDE (R-12 MIN.) INSULATION ON ALL ABOVE CEILING DUCTWORK ROUTED IN UNCONDITIONED SPACE.
5. COORDINATE LOCATIONS OF CEILING GRILLES, REGISTERS, AND DIFFUSERS WITH OVERHEAD PLUMBING PIPING ROUTING.
6. VENTILATION PROVIDED BY RTU ECONOMIZER SET TO 20% MIN. OSA
7. ENVIRONMENTAL FANS SHALL NOT TERMINATE CLOSER THAN 3 FEET ADJACENT TO BUILDING OPENINGS.
8. PROVIDE FIRE-RATED DAMPERS AT ALL CEILING DIFFUSERS AND GRILLES TO MAINTAIN FIRE-RATED ASSEMBLY.

KITCHEN NOTES

1. ALL GREASE EXHAUST DUCTWORK TO COMPLY WITH UL 181 AND CLOSURE SYSTEM SHALL BE PER UL 181B. IMC 603.6
2. GREASE DUCTS MUST BE A MINIMUM OF 12"X12". PER IMC 506.3.9
3. CLEANOUTS TO BE PROVIDED IN GREASE DUCTWORK. SPACING TO BE NO MORE THAN 20 FT APART AND NO MORE THAN 10 FT FROM CHANGES IN DIRECTION OVER 45°. IMC 506.3.9.
4. ALL CLEANOUTS IN GREASE EXHAUST DUCTWORK TO HAVE RATING NOT LESS THAN 1500 F. IMC 506.3.8.
5. PROVIDE A PERFORMANCE TEST AS WELL AS A CAPTURE AND CONTAINMENT TEST FOR ALL TYPE I HOOD SYSTEMS. THE CAPTURE AND CONTAINMENT TEST IS A VISUAL FIELD TEST WITH THE INSPECTOR. THE PERFORMANCE TEST INVOLVES TESTING AND BALANCING BY A QUALIFIED THIRD PARTY. TESTING AND BALANCING REPORTS REQUIRED AT TIME OF FINAL INSPECTION. IMC 507.6
6. PROVIDE A "LIGHT TEST" FOR ALL GREASE DUCTS PRIOR TO ENCLOSING OR CONCEALING. IMC 506.3.2.5
7. THE PERMIT HOLDER SHALL PROVIDE THE NECESSARY TEST EQUIPMENT AND DEVICES REQUIRED TO TEST THE EQUIPMENT. IMC 507.6
8. GREASE DUCT WRAP SHALL EXTEND FROM 18 INCHES BELOW ANY COMBUSTIBLE TRUSS OR WOOD JOIST TO A POINT 18 INCHES ABOVE THE SURFACE OF THE ROOF COVERING OR PROVIDE AN 18 INCH CLEARANCE TO COMBUSTIBLE MATERIAL FOR THE SAME DISTANCE OR PROVIDE A NON-COMBUSTIBLE ONE-HOUR FIRE-RATED SHAFT WITH GYP BOARD AND 3 INCHES MINIMUM REQUIRED CLEARANCE.

MECHANICAL PLAN-BUILDING 'D'

SCALE: 1/4" = 1'-0"



Donald L. Welch
Architect
7533 Sandy Land Lane
Midvale, Utah 84047
801.548-6391
dwlch5977@msn.com




324 S. State St., Suite 400
Salt Lake City, UT 84111
800-678-7077
801-328-5151
fax: 801-328-5155
www.spectrum-engineers.com

THE DESIGNS SHOWN AND DESCRIBED HEREIN INCLUDING ALL TECHNICAL DRAWINGS, GRAPHIC REPRESENTATION & MODELS THEREOF, ARE PROPRIETARY & CAN NOT BE COPIED, DUPLICATED, OR COMMERCIALY EXPLOITED IN WHOLE OR IN PART WITHOUT THE SOLE AND EXPRESS WRITTEN PERMISSION FROM DONALD L. WELCH ARCHITECT

THESE DRAWINGS ARE AVAILABLE FOR LIMITED REVIEW AND EVALUATION BY CLIENTS CONSULTANTS, CONTRACTORS, GOVERNMENT AGENCIES, VENDORS, AND OFFICE PERSONNEL ONLY IN ACCORDANCE WITH THIS NOTICE.

consultant:



project:

Tenant Finish
for New
Brighton
Recovery
Campus
4905, 4911, 4915,
4925, 4931, & 4953
South 900 East
Salt Lake County,
Utah

date

April 24, 2017

revisions

- PERMIT SET-December 28, 2016
- ADDENDUM #1-January 04, 2017
- ADDENDUM #3-January 11, 2017
- ADDENDUM #4-January 17, 2017
- ADDENDUM #5-January 20, 2017
- ADDENDUM #7-February 24, 2017
- ADDENDUM #8 - March 20, 2017
- ADDENDUM #9 - April 11, 2017

data

project no:

drawn by:


checked by:

title

MECHANICAL
PLAN
BUILDING 'D'
sheet

M1D

BUILDING 'D'



PLUMBING PLAN-BUILDING 'D'
SCALE: 1/4" = 1'-0"

KEYED NOTES

- P1 PROVIDE AIR ADMITTANCE VALVE WITHIN CABINETS AT THIS LOCATION. INSTALL PER MANUFACTURER'S RECOMMENDATIONS.
- P2 LOCATION OF HOT WATER CIRCULATION PUMP. INSTALL PER MANUFACTURER'S RECOMMENDATIONS. PROVIDE CIRCUIT SETTERS AT FIXTURES AS REQUIRED TO ALLOW FOR HOT WATER CIRCULATION.
- P3 NEW WATER HEATER. DIRECT T&P VALVE INTO FLOOR DRAIN. CONTINUE TO NEW FIXTURES AND PROVIDE ISOLATION VALVES AT EACH FIXTURE. PROVIDE GAS LINE ISOLATION VALVE AND SEISMIC BRACING. PROVIDE FLUE AND INTAKE PIPING PER SCHEDULE AND TERMINATE THROUGH ROOF WITH CONCENTRIC VENT KIT.
- P4 NEW URINAL. TIE INTO NEW WASTE, VENT, AND DOMESTIC COLD WATER PIPING. SEE PLUMBING SCHEDULE FOR FIXTURE PIPING SIZES.
- P5 NEW SINK. TIE INTO NEW WASTE, VENT, AND DOMESTIC HOT/COLD WATER PIPING. SEE PLUMBING SCHEDULE FOR FIXTURE PIPING SIZES.
- P6 NEW KITCHEN SINK. TIE INTO NEW WASTE, VENT, AND DOMESTIC HOT/COLD WATER PIPING. SEE PLUMBING SCHEDULE FOR FIXTURE PIPING SIZES. PROVIDE RECESSED WALL BOX FOR REFRIGERATOR COLD WATER CONNECTION. PROVIDE HOT WATER CONNECTION TO SERVE DISHWASHER.
- P7 LOCATION OF NEW WATER CLOSET. PROVIDE WATER, WASTE & VENT CONNECTION. SEE PLUMBING SCHEDULE FOR FIXTURE PIPING SIZES.
- P8 LOCATION OF NEW LAVATORY. PROVIDE WATER, WASTE, & VENT CONNECTION. SEE PLUMBING SCHEDULE FOR FIXTURE PIPING SIZES.
- P9 LOCATION OF NEW FLOOR DRAIN. PROVIDE WASTE & VENT CONNECTION. SEE PLUMBING SCHEDULE FOR FIXTURE PIPING SIZES.
- P10 SEE CIVIL PLANS FOR CONTINUATION.
- P11 PROVIDE COLD WATER ENTRY WITH BACKFLOW PREVENTER. REFERENCE SHEET P02 FOR DEVICE MAKE/MODEL.
- P12 PROVIDE 4" FIRE ENTRY DOUBLE CHECK DETECTOR ASSEMBLY. REFERENCE SHEET P02 FOR DEVICE MAKE/MODEL. PROVIDE POWER (115V) FOR RISER MOUNTED COMPRESSOR & PRESSURE SWITCH. REFERENCE SHEET P13 FOR DETAILS. INSTALL COMPRESSOR ABOVE HEIGHT OF DOOR HEADER TO KEEP OUT OF TRAVEL PATH.
- P13 PROVIDE 3" VENT THROUGH ROOF.
- P14 PROVIDE WALL CLEANOUT AT THIS LOCATION.
- P15 PROVIDE GAS LINE WITH VENTLESS REGULATOR AND ISOLATION VALVE. CONNECT TO UNDERSIDE OF NEW RTU. NO ROOF PENETRATION REQUIRED WITH RTU MODEL SPECIFIED.
- P16 PROVIDE GAS LINE TO FLUELESS DECORATIVE FIREPLACE (20 MBH). INSTALL PER MANUFACTURER'S RECOMMENDATIONS.
- P17 PROVIDE EMERGENCY FUEL SHUTOFF SWITCH NEAR KITCHEN HOOD. SWITCH TO CLOSE GAS LINE SOLENOID VALVE ASSOCIATED WITH ALL GAS-FIRED APPLIANCES IN KITCHEN.
- P18 ROUTE 1/2" CW, HW, & HWC LINES BELOW FLOOR TO ISLAND KITCHEN SINK AT THIS LOCATION. EXTEND 1/2" HW LINE TO ADJACENT DISHWASHER.
- P19 ROUTE CW LINE TO REFRIGERATOR WATER CONNECTION. PROVIDED RECESSED WALL BOX WITH ISOLATION VALVE.
- P20 PROVIDE PIPING TRANSITIONS UNDER STRUCTURAL BEAM AS REQUIRED. (TYPICAL)
- P21 ROUTE CW, HW, & HWC LINES TO CLOTHES WASHER WALL BOX. PROVIDE INTEGRAL ISOLATION VALVES AND WATER HAMMER ARRESTOR.
- P22 ROUTE 1-1/2" CW, 3/4" HW, & 1/2" HWC LINES TO BATHROOM GROUP. PROVIDE HOT AND COLD WATER ISOLATION VALVES AT LAVATORIES.
- P23 ROUTE 3/4" CW, 3/4" HW, & 1/2" HWC LINES TO MOP SINK/SINK.
- P24 COMBINE VENT PIPING FROM BATHROOM FIXTURE AND TERMINATE THROUGH ROOF AT THIS LOCATION. MULTIPLE BATHROOMS GROUPS CAN BE GROUPED TO MINIMIZE ROOFING PENETRATIONS IF NEEDED. ALL VENT THROUGH ROOF PENETRATIONS TO BE 3" MINIMUM.
- P25 CONTINUE WASTE LINE TO ADJACENT FIXTURE GROUPS. REFERENCE PLUMBING FIXTURE SCHEDULE FOR INDIVIDUAL FIXTURE WASTE LINE SIZES.

Donald L. Welch
Architect
7533 Sandy Land Lane
Midvale, Utah 84047
801.548-6391
dwelch5977@msn.com




324 S. State St., Suite 400
Salt Lake City, UT 84111
800-678-7077
801-328-5151
fax: 801-328-5155
www.spectrum-engineers.com

THE DESIGNS SHOWN AND DESCRIBED HEREIN INCLUDING ALL TECHNICAL DRAWINGS, GRAPHIC REPRESENTATION & MODELS THEREOF, ARE PROPRIETARY & CAN NOT BE COPIED, DUPLICATED, OR COMMERCIALY EXPLOITED IN WHOLE OR IN PART WITHOUT THE SOLE AND EXPRESS WRITTEN PERMISSION FROM DONALD L. WELCH ARCHITECT

THESE DRAWINGS ARE AVAILABLE FOR LIMITED REVIEW AND EVALUATION BY CLIENTS, CONSULTANTS, CONTRACTORS, GOVERNMENT AGENCIES, VENDORS, AND OFFICE PERSONNEL ONLY IN ACCORDANCE WITH THIS NOTICE.

consultant:



project:

Tenant Finish
for New
Brighton
Recovery
Campus
4905, 4911, 4915,
4925, 4931, & 4953
South 900 East
Salt Lake County,
Utah

date

April 24, 2017

revisions

- PERMIT SET-December 28, 2016
ADDENDUM #1-January 04, 2017
ADDENDUM #3-January 11, 2017
ADDENDUM #4-January 17, 2017
ADDENDUM #5-January 20, 2017
ADDENDUM #7-February 24, 2017
ADDENDUM #8 - March 20, 2017
ADDENDUM #9 - April 11, 2017

data

project no:

drawn by:

checked by:

title

PLUMBING
PLAN
BUILDING 'D'
sheet

P1D

BUILDING 'D'