

ADVANTAGE[®]

**Introducing a New Line of
Quality Fire Extinguishers
from Badger!**



- Faster to Service
- Easy To Read 2-piece Nameplate
- Square Thread Valve Design
- Heavy Duty Metal Siphon Tube
- No-Scratch Hose Strap
- Large Pull Pin



ADVANTAGE

- Full range - 2.5#, 5.5#, 10# and 20# rechargeable models.
- Aluminum valves, handles and levers are lightweight yet extremely durable and corrosion resistant.
- Heavy duty plated steel siphon tubes are threaded versus crimped providing a secure connection.
- Large neck opening more easily accomodates recharge.
- Color coded nameplates make it easier to identify agent type and applications.
- Engineered grade polymer hose strap does not bend or scratch cylinders.
- Square thread design makes removing and installing valve quick and easy.
- Large pull pin and handles are easy to operate with gloves.
- 2.5# and 5.5# cylinder geometry provides quicker drying after hydro-test.



Recyclable aluminum cylinders, valves, handles and levers represent higher recycle value.

MODEL	ADV-250	ADV-550	ADV-10	ADV-20
PART NUMBER	21007865	21007866	21007867	21007868
NOMINAL CAPACITY (lb.)	2.5	5	10	18
UL FIRE RATING	1-A:10-B:C	3-A:40-B:C	4A:60-B:C	6-A:80-B:C
AGENT TYPE	ABC	ABC	ABC	ABC
CYLINDER MATERIAL	ALUMINUM	ALUMINUM	STEEL	STEEL
VALVE MATERIAL	ALUMINUM	ALUMINUM	ALUMINUM	ALUMINUM
HANDLE/LEVER MATERIAL	ALUMINUM	ALUMINUM	ALUMINUM	ALUMINUM
RECHARGE EXPELLANT	NITROGEN	NITROGEN	NITROGEN	NITROGEN
OPERATING PRESSURE @ 70°F	100	195	195	195
TEMPERATURE RANGE (°F)	-40 to 120	-40 to 120	-40 to 120	-40 to 120
TEMPERATURE RANGE (°C)	-40.0 to 48.9	-40.0 to 48.9	-40.0 to 48.9	-40.0 to 48.9
NOM. AGENT FLOW RATE (lb./sec)	0.32	0.42	0.60	0.78
NOM. AGENT FLOW RATE (kg/sec)	0.15	0.19	0.27	0.35
NOM. DISCHARGE TIME (sec)	10.0+/-1.5	14 +/-1.0	21.1 +/-2.0	25.0 +/-2.0
DISCHARGE RANGE (ft.)	10.0-15.0	12.0-18.0	16.0-20.0	16.0-20.0
DISCHARGE RANGE (m)	3.0-4.6	3.7-5.5	4.9-6.1	4.9-6.1
UNIT HEIGHT (in.)	15	16.4	19.6	21.7
UNIT HEIGHT (cm)	38.1	41.65	49.7	55.11
UNIT WIDTH (in.)	5.5	7.5	8	9
UNIT WIDTH (cm)	13.97	19.05	20.32	22.86
UNIT DEPTH (in.)	3.25	4.5	5.21	7.1
UNIT DEPTH (cm.)	8.25	11.43	13.23	18.03
SHIPPING WEIGHT (lb.)	5	9.5	17.5	31.45
SHIPPING WEIGHT (kg)	2.27	4.31	7.94	14.27
USCG APPROVAL	Type B:C Size I	Type A, Size II Type B:C, Size I	Type A, Size II Type B:C, Size II	Type A, Size II Type B:C, Size II
BRACKET	466401 (Included)	466400 (Optional)	366242 (Optional)	292474 (Optional)