



# FDC

## Siamese Ductile Iron

ED

Fire Suppression Services Incorporated  
3802 South 2300 East, Salt Lake City, UT 84109. Ph (801) 277-6464



### Two-Way with Single Clapper

**Function:** Used as an auxiliary inlet connection providing 500 GPM/1892 lpm minimum to supplement the fire protection water supply. Swing clapper provides unobstructed waterway. Exposed design is an economical method of satisfying fire dept inlet requirements.

**Regularly Furnished:** Cast brass two-way inlet body, swing clapper and pin lug swivel. Back or angle outlet as selected by model number. Lettering as selected. Size 4"/10.2cm X 2½" X 2½"/6.4cm X 6.4cm.

#### Optional Finishes:

- B Polished Brass
- C Rough Chrome Plated
- D Polished Chrome Plated

#### Lettering Available:

Auto Spkr or Standpipe

**Specify:** Thread and lettering

[http://www.potterroemer.com/component/page.shop.product\\_details/flypage.shop.flypage/product\\_id,447/option.com\\_virtuemart/Item\\_id,4/](http://www.potterroemer.com/component/page.shop.product_details/flypage.shop.flypage/product_id,447/option.com_virtuemart/Item_id,4/)

**This document is confidential & may not be shared or distributed to other parties without the express permission of Fire Suppression Services Inc.**